



Lutz B2 Vario

Light weight, safe, practical.

With gradually variable speed controller to enable transfer of small amounts of liquid.

> For the laboratory and research sector

The innovation for increased safety and ease of use

The Lutz B2 Vario: Perfect for the laboratory and research sector



Lutz B2 Vario stands for: Versatile, maximum possible safety, and optimum price-performance ratio.

Environmental protection, safety, energy, cost consciousness, and easy handling: the demands which a pump has to meet are growing more and more. Simplicity and ease of handling must be inherent characteristics as well. At Lutz, we have met this challenge and have developed a pump which lives up to these expectations. The new electric drum and container pump "Lutz B2 Vario" incorporates a reliable and tested technique together with a number of new functions providing perfect fluid management solutions, whatever industry you are in.

The advantages of B2 Vario:

- ✓ **Variable speed motor** with safety cut-off to enable the transfer of liquids in small amounts
- ✓ Easy and safe to operate by integrated ergonomically designed handles and nozzle
- ✓ Ultra quiet, long service life
- ✓ **Different lengths available** 19", 27" and 39" for the use in small vessels up to 55 gal. drums
- ✓ Wide range of applications possible due to sealless construction
- ✓ Service-friendly and simple to dismantle
- Available in polypropylene and stainless steel 316





Sealless pump tube, lube-free, thus no contamination of the liquid. Service-friendly construction, simple to dismantle and improved drainage function.







Hook for storing nozzle and power cord at the pump

Safety First




Personal safety and the environment are of vital importance when it comes to handling chemicals, acids, alkalis or other dangerous liquids, particularly when transferring small

amounts of liquid. The new "Lutz B2 Vario" provides a complete solution. The infinitely variable speed controller with integrated on/off switch allows a controlled and comfortable filling of smaller and larger liquid amounts. The operator can gradually regulate the delivery rate from lowest up to requested speed by one movement of the hand.



Motor: 180 W, 110-120 V, 60 Hz Pump tube: polypropylene (PP) or stainless steel (316)

Max. Capacity: 18.5 GPM
Max. Pressure: 21.3 ft
Specific Gravity: max. 1.3
Viscosity: max. 300 cps
Weight: 4.9 – 7.7 lbs



	For emptying of cans and drums		Lutz B2 Vario PP-SL in polypropylene* Pump	Lutz B2 Vario PP-SL in polypropylene** Pump Set	Lutz B2 Vario SS-SL in stainless steel* Pump	Lutz B2 Vario SS-SL in stainless steel** Pump Set
Î	Length 19"	Order No.	0201-520	0205-060	0201-540	0205-070
E	Length 27"	Order No.	0201-521	0205-061	0201-541	0205-071
	Length 39"	Order No.	0201-522	0205-062	0201-542	0205-072

^{**} The pump set comprises: pump, PVC-hose, wall bracket and nozzle made of polypropylene.

^{*} Pump Lutz B2 Vario with threaded connection 1" and hose connection 3/4"



Lutz does not leave anything to chance





The Lutz B2 Vario stands for innovative technology, simplicity, and maximum safety.

Ultra quiet and convenient

Compelling characteristics of the pump are the ultra quiet running and the long service life. The sealless pump tube features the proven technology of thousands of pumps used for transfer applications in the industry. The new development Lutz B2 Vario covers a large field of applications, has a service friendly construction, and an improved drainage function.

Complete pump sets save time and money

The pump set comprises a pump,
5 ft PVC-hose, nozzle and wall bracket,
supplied ready for use.
The pump can be optionally

The pump can be optionally equipped with a flow meter.







Lutz offers the

optimum

solution for

professional

Fluid Management

Lutz Pumps, Inc.

1160 Beaver Ruin Road Norcross, GA 30093-4898 Phone: (770) 925-1222 (800) 843-3901 (770) 923-0334 Fax:

www.lutzpumpsamerica.com e-mail: info@lutzpumpsamerica.com