

Safe and economic emptying of canisters, drums and containers

- Manual hand pumps
- Laboratory pumps
- Drum and container pumps
- Accessories for pumps
- Eccentric screw pumps for barrels and containers

Made in Germany



For oils,
chemicals,
flammable and
high viscous
media

BARRELPUMP.IR



Made in Germany



ATEX 2014/34/EC



Proofed Quality

Management System ISO 9001:2015
www.tuv.com ID: 9105019828

Decades of experience in barrel pump business

The family-run company JESSBERGER headquartered in Ottobrunn near Munich is manufacturer of electric and pneumatic driven drum and container pumps, vertical and horizontal eccentric screw pumps, dosing pumps for high viscous media, hand operated pumps and a comprehensive range of accessories like flowmeters, nozzles, etc.

Air operated diaphragm pumps, horizontal centrifugal pumps (also available as magnetically coupled sealless centrifugal pumps) and vertical centrifugal pumps complete the delivery program beside further industrial pumps.

Thanks to long time employees and the firm owners the company pides itself on a long and substantial experience in pump business. Although the brand JESSBERGER exists as a firm name in drum pump business only since beginning 2003, the company has developed within a short time to a real alternative. The intention was to set new standards in price at

The good reputation of JESSBERGER in drum pump business is a result of a personal, expert advice through our team, a maximum flexibility in all areas of the company and a direct contact with the customers.

The company owners have set themselves the goal of having a very close and personal contact with their customers – not only by exhibiting on many trade shows each year. Furthermore, they want to demonstrate their flexibility that is based on a clear arranged company structure at delivery times and special customers' requests.

Qualified partners in Germany, Europe and all over the world complete this concept and guarantee a nearly optimized customer support.

The company leadership and the technical management attach the greatest importance to a strict quality control. The complete pro-



duction and assembling area are organized in accordance to the quality management system DIN EN ISO 9001:2015 and for the Stainless steel pump tubes, the electric Ex-motors JP-400, 440, 460, 480, the air operated motors JP-AIR 1, JP-AIR 2 and JP-AIR 3 and some eccentric screw pumps in accordance to ATEX 2014/34/EC (explosion prevention and protection).

Annual external and internal inspection audits assure the compliance with these regulations and ensure the high quality standards. This pronounced awareness of quality and the experience for decades in drum pump business guarantee a high quality of the pumps at a very attractive price.

Convince yourself of the advantages of JESSBERGER and the quality made in Germany!

Our advantages

- Owner operated family company
- Decades of experience in drum pump business
- Quality made in Germany
- Optimal price/performance ratio
- Personal and expert advice, the best possible customer service
- Maximum flexibility in all company divisions
- Certified acc. to ISO 9001:2015 and ATEX 2014/34/EC

coexisting highest quality – which was succeeded impressively.

Since March 2008 the pump manufacturer has its new head office in Ottobrunn. In February 2018, the available industrial area more than doubled due to the acquisition of the neighbouring building. More than 900 sqm production/stock and 700 sqm office will ensure a further sustained economic growth and the possibility to fulfill special customers' requests. The construction and production of the eccentric screw pumps are based at a second facility in Upper Bavaria.

BARRELPUMP.IR

Contents

Manual hand pumps

Laboratory pumps

Drum pumps

Eccentric screw pumps

4 Introduction to JESSBERGER hand pumps, laboratory pumps and drum pumps

5 The pump tube materials and their applications

6–10 Manual hand pump for thin fluid media up to 1.000 mPas

- Plastic hand pumps for chemicals like acids and alkalis or mineral oil products
- Stainless steel hand pump for flammable media
- Hand crank rotary pumps or hand lever pumps for mineral oil products
- Fire brigade hand pump
- Battery driven pump
- Thread adapters

11–23 Laboratory pumps made of Polypropylene for acids and alkalis or Stainless steel for neutral, lightly aggressive media or thin fluid food up to 400 mPas:

- Drives and pump tubes for laboratory pumps
- Complete laboratory pumps
- Accessories for laboratory pumps
- Laboratory pump sets

24–52 Electric or air operated drum and container pumps for thin fluid, neutral, aggressive or flammable media up to 1.000 mPas:

- Drives for drum pumps: electric motors or air operated motors
- Sealless pump tubes of Polypropylene (for acids and alkalis), PVDF (for highly aggressive media), Aluminium (for mineral oil products) and Stainless steel (for flammable media or food)
- Mixing pump tubes of Polypropylene or Stainless steel
- Pump tube with mechanical seal or complete drum emptying function - each made of Stainless steel
- Drum pump sets

53–55 Vertical eccentric screw pumps and container pumps for highly viscous media up to 100.000 mPas:

- Series JP-700 SR with alternating current motors or air operated motors up to 10.000 mPas
- Series JP-700 DR, JP-700FK with three phase motors, air operated vane motors, gear motors or single-phase motors up to 100.000 mPas
- Container pumps with a capacity of 80, 200 or 300 l/min

56 The complete product range

BARRELPUMP.IR


Introduction to JESSBERGER hand pumps, laboratory pumps and drum pumps

Manual hand pumps

are always a useful and cost effective alternative to conventional electric or air operated drum pumps when only small quantities of media have to be removed out of canisters or drums or if the customer would use the drum pump only occasionally or rarely.

Depending on the medium different pump tube materials and gaskets are available. In principle the hand pump can be divided into three groups: for chemicals such as acids, alkalis and detergents for mineral oil products and for flammable liquids such as gasoline or solvents. The maximum viscosity of the pumped fluids for the hand pumps is 1.000 mPas.

Most hand pumps have a barrel thread of 2" (partially available with the optional accessory) and can therefore be screwed in all the 60 and 200 liter steel drums. For plastics drums and cans various thread adapters for compensation are available.



Electric or air operated laboratory pumps

are an economical and safe solution for the filling and transferring of small quantities of neutral or aggressive media and thin fluid food from cans, drums or containers.

The laboratory pumps consist of a light, handy and powerful electric motor or air operated motor and a pump tube suitable for the application and available in different materials, pump tube diameters and pump tube lengths. With the universal motor JP-140, the maximum density of the media is 1,4, and the maximum viscosity 400 mPas.

Because of their lightweight and simplest operation, the laboratory pumps are used everywhere where the transferring of small quantities of media is part of the daily business. They have proven themselves in addition to the industry also in laboratories or pharmacies.

Electric or air operated drum and container pumps

by JESSBERGER are lightweight, handy and very powerful devices for an economical and safe filling and transferring of thin to medium viscous media, neutral or aggressive, non-flammable or flammable substances out of drums and containers.

Our drum pumps can be flexibly used for emptying drums and containers, in plant engineering or in filling processes. They are designed ideally for intermittent, short-time operation. The sophisticated, technically clear construction ensures an efficient and safe use.

Drum and container pumps consist of a high-performance, internally or externally ventilated universal motor, which is also available in an explosion-proof version and a pump tube that is suitable for the application. The pump tubes of drum pumps are available in Polypropylene (for aggressive media as cleaning agents, acids and alkalis, up to 50 °C), PVDF (for highly aggressive media or when the medium temperature is between 50 and 90 °C), Aluminium (for mineral oil products) or Stainless steel 316Ti (for flammable liquids such as gasoline or solvents or thin liquid food). Different tube lengths, mixing tubes (for simultaneously mixing and pumping), sealless versions or stainless steel versions with mechanical seals and optional residues emptying function are all on hand.

With the universal motor JP-280, the maximum density of the media is 1.9 and the maximum viscosity is 1.000 mPas.

As drives, universal motors and air operated motors are available.



BARRELPUMP.IR

The various pump tube materials and their applications range in the overview

Pump tubes made of Polypropylene (PP)

are suitable for neutral, aggressive and hardly combustible liquids. They are used specifically for pumping aggressive chemicals such as acids, alkalis or detergents.

Drive shaft: Stainless steel 316Ti or Hastelloy 2.4610

Media temperature: max. 50 °C

Media: Formic acid (50%), ammonia, boric acid, distilled water, liquid fertilizers, ferric-II and III-chloride, acetic acid (80%), photo developers, fruit acids, potassium hydroxide, copper chloride, lactic acid, sodium hydroxide, phosphoric acid, hydrochloric acid, sulfuric acid (up to 90%), hydrogen peroxide, citric acid and many other media.

Pump tubes made of Polyvinylidenfluorid (PVDF)

are especially suitable for highly aggressive liquids such as concentrated acids and bases.

Drive shaft: Hastelloy 2.4610

Media temperature: max. 90 °C

Media: Hydrobromic acid, perchloric acid, chromic acid, hydrofluoric acid, sodium hypochlorite, nitric acid and sulfuric acid (> 90%).

Also all media that are listed at the pump tubes made of Polypropylene can be handled.

Pump tubes made of Aluminium (ALU)

are suitable for neutral and hardly combustible liquids. With these pump tubes particularly mineral oil products up to a maximum viscosity of 1.000 mPas will be transferred.

Drive shaft: Stainless steel 316Ti

Media temperature: max. 90 °C

Media: Drilling emulsions, diesel, liquid wax, liquid soap, gear oils, heating oil, hydraulic oils, machine oils, mineral oils and motor oils.

Pump tubes made of Stainless steel 316Ti (SS)

are used for all neutral, lightly aggressive liquids such as diluted acids, alkalis or detergents and thin fluid food. In addition the pump tubes provide a special safety for conveying or transferring flammable liquids of different hazard classes (up to temperature class 4) in the Ex-zone 0 and when pumping low-viscous neutral or lightly aggressive media in Ex-zones 1 and 2.

Drive shaft: Stainless steel 316Ti

Media temperature:

max. 90 °C (with PTFE rotor), max. 120 °C (with rotor made of Stainless steel solid material)

Media: Acetone, alcohol, ammonia, gasoline, flammable solvents, potassium hydroxide, sodium hydroxide nitrocellulose lacquers, perchlorethylene, phosphoric acid, sulfuric acid (up to 7.5% and over 90%), trichlorethylene, toluene.

In addition the Stainless steel pump tubes are suitable for pumping thin fluid food such as fruit juices, milk, edible oils and for all media that are mentioned at Aluminium tubes.

We will be pleased to advise you regarding chemical resistance.

Please ask us.



▶ PP

▶ PVDF

▶ Aluminium

▶ Stainless steel

BARRELPUMP.IR

Manual hand pumps



Hand pump JP-02

Hand pump for acids, alkalis and water-based chemicals.

Pump material: Polypropylene

Shaft: Stainless steel 304

Seals: FKM

Flow rate: 0,3, 0,37 or 0,45 l/stroke*, depending on lever position

The telescopic suction tube is adjustable from 340 to 900 mm and has a diameter of 40 mm. The pump housing has two threads G 2" and G 1½".



Order No.: 6002 0000



Hand pump JP-03

Hand pump for oils, diesel, alcohol up to max. 50%, antifreeze liquid (diluted), water, etc.

Pump material: Polypropylene

Shaft: Tool steel

Seals: NBR

Flow rate: 0,3, 0,37 or 0,45 l/stroke*, depending on lever position

The telescopic suction tube is adjustable from 340 to 900 mm and has a diameter of 40 mm. The pump housing has two threads G 2" and G 1½".



Order No.: 6003 0000



Hand pump JP-04

Hand pump for different media

Pump material: Polypropylene

Shaft: Polypropylene

Seals: depending on the execution

Flow rate: ca. 0,3 l/stroke*

Hose connection: ¾"

The telescopic suction tube is adjustable from 500 to 950 mm and has a diameter of max. 34 mm.

The pump housing has a thread in 2" to be screwed in all standard steel drums. To compensate different threads we can offer appropriate threaded adapters.

JP-04 **YELLOW** seals: FKM

For aggressive media such as acids and alkalis

JP-04 **BLUE** seals: NBR

For mineral oil products

JP-04 **RED** seals: EPDM

For alkaline solutions

JP-04 **BLUE/WHITE**

seals: Fluoropolymer

For thin fluid food



Order No.: YELLOW: 6004 0000, BLUE: 6004 0001, RED: 6004 0002, BLUE/WHITE: 6004 0003

Manual hand pumps



Hand pump JP-05

Suitable for flammable liquids such as solvents (including acetone!) and low viscous food.

Pump tube made of Stainless steel V4A (316Ti), all gaskets made of PTFE. Therefore especially suitable for flammable liquids such as solvents (incl. acetone).

Certified: risk analysis made by TUEV Munich

Suction tube lengths: 700 and 1.000 mm
Flow rate: 0,3–0,6 l/stroke*

Necessary accessories	Order No.:
Discharge arc with PTFE seal and wing nut	
Ø 11 mm	6510
Ø 25 mm	9074
Hose connection made of Stainless steel, with PTFE seal and wing nut made of Brass, nickel plated	
Hose connection ¾"	6520
Hose connection 1"	6530
Drum adapter made of Brass nickel plated R2" with locking device	6540
Anti-static set	9003
consisting of 4 copper cables (absolutely necessary when pumping flammable liquids)	

Order No.: 700 mm: 6005 0700, 1.000 mm: 6005 1000 plus optional accessories



Plastic hand pump JP-06

Suitable for water, lightly aggressive acids and alkalies.

Pump material: Polyethylen and PVC
Flow rate 0,08 l/pumping process and 18,5 l/min at an independent transferring*
Pump tube length: 850 mm
Pump tube diameter: 25 mm

Thread adapter: G 2"

This hand pump is designed as a siphon pump and comes with 1.300 mm long discharge hose. After the suction pipe and discharge hose had been filled manually, the pump works independently.

Order No.: 6006 0000



Hand pump JP-07

Manual filling and transfer pump

Pump body made of Polypropylene, internal parts also made of Stainless steel, suitable for 20 liter canisters up to 200 liter drums. Three adapters for bung hole diameters from 46,5 to 60 mm and a four-piece suction tube are included.

Flow rate: Water: 20 l/min*
 Oil SAE 30: 9 l/min at 20 °C*
Pump tube length: Suction pump consisting of four parts, each 250 mm
Pump tube diameter: max. 31 mm

Temperature: 40 °C*
Viscosity: 400 mPas*

JP-07 **BLUE** seals: NBR
 For mineral oil products
 JP-07 **RED** seals: EPDM
 For alkaline solutions
 JP-07 **GREEN** seals: FKM
 For light acids

Accessories	Order No.:
Transfer hose (1.5 m) with nozzle:	
JP-07 BLUE	6710
JP-07 RED	6720
JP-07 GREEN	6730

Order No.: BLUE: 6007 0001, RED: 6007 0002, GREEN: 6007 0003 plus optional accessories

* All specified values are real measured maximum values.
 The flow rate of the pump refers to water at 18 °C and free outlet.

Manual hand pumps



Hand pump JP-08

Hand-crank rotary pump for chemicals

The pump is suitable for thin fluid, highly aggressive media such as acids and alkalies.

Pump material: PVDF

Seals: PTFE

Flow rate: 0.3 l/rotation*

Suction tube length: 3 x 35 cm

The pump comes with discharge arc and drum adapter G 2".

Regular lubrication required.

Order No.: 6008 0000



Hand pump JP-09

Suitable for almost all thin liquid and lightly aggressive media such as acids, alkalis and chemicals. Better resistance compared JP-02 due to a PP shaft.

Pump material: Polypropylene

Telescopic suction tube: 3 parts, Polyethylene

Seals: FKM

Pump tube length: for containers to 960 mm

Flow rate: 0,5 l/stroke*

Weight: 1.2 kg

PE hose 2 m

Thread G 2" for screwing in standard steel barrels.

Adapters available for plastics drums and cans of 60–220 l.

Outlet piece DN 19, 3/4".

The pump is not to be used for pumping media of hazard classes A1/A11, other flammable media or in an explosive environment.

Order No.: 6009 0000



Hand pump JP-11

Hand-crank rotary pump

The pump is suitable for thin fluid, non-flammable liquids such as diesel, gear oil, heating oil, hydraulic oil, machine oil, mineral oil, motor oil, etc. up to 1.000 mPas.

The pump is not suitable for water.

Pump material: Aluminium and steel

Seals: NBR

Flow rate: 1 l/rotation*

Optimal dosing possible through forwards and backwards transferring with hand level.

Pump tube length: 1.080 mm

Pump tube diameter: 32 mm

Strainer diameter: 52 mm

Head: 15 m*

Horizontal distance: 50 m*

Pump complete with discharge hose 1.350 mm, drum adapter G 2" and strainer.

Order No.: 6011 0000



Hand pump JP-12

Hand-crank rotary pump

The pump is suitable for thin fluid, non-flammable liquids such as diesel, gear oil, heating oil, hydraulic oil, machine oil, mineral oil, motor oil, etc. up to 1.000 mPas.

The pump is not suitable for water.

Pump material: Aluminium and steel

Seals: NBR

Flow rate: 1 l/rotation*

Optimal dosing possible through forwards and backwards transferring with hand level.

Pump tube length: 1.080 mm

Pump tube diameter: 32 mm

Strainer diameter: 52 mm

Head: 15 m*

Horizontal distance: 50 m*

Pump with special mineral oil hose 2.000 mm, discharge arc drum adapter G 2" and strainer.

Order No.: 6012 0000

BARRELPUMP.IR

Manual hand pumps



Hand pump JP-13

Metal hand-crank rotary pump

The pump is suitable for diesel, heating oil, oils (up to SAE 90) and all other self-lubricating, non-aggressive and non-flammable media.

The pump is not suitable for water.

Pump material: pump housing of cast iron
Seals: NBR

Flow rate: 0,25 l/rotation*

Pump tube diameter: max. 30 mm

Strainer diameter: max. 40 mm

Suction tube length: 1.000 mm three parts for smaller containers and 200 liter drums

Pump including discharge arc, drum adapter G 2" and strainer.

Order No.: 6013 0000



Hand pump JP-14

Hand lever pump made of metal

The pump is suitable for thin-liquid, non flammable media like diesel, machine oils, mineral oils, etc.

Material: Metal, zinc alloy

Seals: NBR

Flow rate: 0,5 l/stroke*

Pump tube length: 450–840 mm

Pump tube diameter: 40 mm

Thread adapter: G 2"

Telescopic suction tube enables a universal use for all sizes of drums.

Order No.: 6014 0000



Hand pump JP-16

Fire brigade hand pump

ATEX compliant, single-acting reciprocating pump that can be used for following media of hazard classes A I-III: diesel, heating oil light/heavy, fuel, petroleum, anti freezing liquid for cooler (undiluted), thin fluid mineral oils and rapeseed methyl ester.

Fire service version with flexible suction hose instead of a rigid tube.

Suction hose DN 19 x 4; 1,5 m

Discharge hose DN 19 x 4; 1,5 m

Flow rate: app. 0,25 l/stroke*

In pump housing integrated drum adapters with M 64x4 and G 2" enable an easy fixing in drum.

Order No.: 6016 0000



Battery driven pump JP-111

Suitable for water, diesel, lightly oils, neutral, lightly aggressive and non flammable media.

Only suitable for short-term operation.

Pump material: PP, PE and ABS

Suction tube length: 460 mm

Discharge hose: 600 mm

Largest suction tube diameter: 33 mm

Flow rate: 8 l/min.*

Driven by batteries, size D, 1,5 V (not included in delivery; available in trade).

Order No.: 6011 0000

BARRELPUMP.IR

* All specified values are real measured maximum values. The flow rate of the pump refers to water at 18 °C and free outlet.



When pumping flammable media or use in explosive environments also in hand pump business only conductive pumps are allowed to be used that hold an ignition source assessment. Furthermore it is mandatory to establish a potential equalization by grounding the hand pump and the drum.

Thread adapters



Thread adapters for equalization of different threads at canisters, drums, containers, etc. when fixing f.e. hand pumps.

In principle, the JESSBERGER hand pumps can be easily screwed into the threads of steel barrels like S 60 or S 200 thanks to their included adapters (2" BSP male thread).

Due to the big variety of different canisters, drums, containers, etc. that are available in the market there is often a need to use an adapter to screw the pump in the vessel securely and fixed.

No.	Color	Thread 1	Thread 2	Order No.
1	Brown	2" BSP fine, internal thread*	DIN 71, internal thread	6001
2	Grey	2" BSP fine, internal thread*	DIN 61/31, external thread	6002
3	Black	2" BSP fine, external thread*	DIN 61/31, external thread	6003
4	Yellow	2" BSP fine, internal thread*	DIN 61/31, internal thread	6004
5	White	2" BSP fine, internal thread*	ASTM Ø 63 mm, int. thread	6005
6	Red	2" Mauser, coarse int. thread*	Trisure coarse, ext. thread	6006
7	Orange	2" BSP fine, internal thread*	Trisure coarse, ext. thread	6007
8	Blue	2" BSP fine, internal thread*	2" Mauser coarse ext. thread	6008
9	Green	2" BSP fine, internal thread*	DIN 51, internal thread	6009
10	Set	All adapters No. 1-9		6010

Classification (without any obligations):

BLUE	External thread Mauser	for 200 liter plastic drums (coarse thread 69 mm)
ORANGE	External thread Trisure	for 200 liter plastic drums (fine thread 56 mm)
YELLOW	Internal thread DIN 61/31	for 30 liter plastic container (59 mm)
BROWN	Internal thread DIN 71	for 60 liter plastic container (71 mm)

We can send you a drawing of the adapters via e-mail.

*2" BSP (british standard pipe) corresponds to a diameter of 58 mm.

BARRELPUMP.IR

Laboratory pumps

Electric or air operated laboratory pumps with a suction tube made of Polypropylene (Ø 25, 28 or 32 mm), Stainless steel 316Ti (Ø 28 or 32 mm) or PVDF (Ø 32 mm)

Electric motor



Laboratory pump tube

With lightweight and easy operation, laboratory pumps make an ideal solution if pumping small quantities of liquids is part of your daily business.

The pumps have proven themselves in pharmacies, laboratories and the chemical trading as economical and safe solution when filling and transferring of acids and alkalies.

Convince yourself of the quality and the optimal cost-performance ratio of the JESSBERGER laboratory pumps!

JESSBERGER laboratory pumps – the economical and safe solution for filling and transferring small quantities of neutral and aggressive media like acids and alkalies.

The particular advantages in an overview:

- Designed for a safe and easy filling of low quantities out of narrow-necked containers and canisters.
- Suitable for almost all thin fluid, neutral or corrosive media, but not for flammable liquids (for Stainless steel pump tube ATEX is in preparation).
- Handiness and good transportability thanks to the low weight.
- The pumps are driven by universal motors or air operated motors.
- Ergonomically designed handle of high-performance electric motor for single-handed operation.
- Sealless pump tubes made of Polypropylene (PP), PVDF and Stainless steel 316Ti with acid and alkali-resistant shaft made of Stainless steel or Hastelloy 2.4610.

Air operated motor

Laboratory pump tube



- Optimal drum emptying through the availability of different suction tube lengths and diameters.
- Hose connection included in delivery; for PP pump tube with Ø 25 mm: hose connection 1/2", for Ø 28 and 32 mm hose connection 3/4"; for SS pump tube for Ø 28 mm hose connection 3/4", for Ø 32 mm hose connection 1"; for PVDF pump tube with Ø 32 mm hose connection 3/4".
- Wide range of accessories as barrel and threaded adapters, media-resistant hoses, nozzles, wall hanger or flow meters available on request (see summary on page 22).
- Quick disconnection of the drive from the pump tube through a few rotations.
- Easy disassembling and easy cleaning of the pump tube.
- Consistent modular system.

Laboratory pump tubes

Polypropylene pump tubes with Stainless steel drive shaft for neutral or lightly aggressive media or with Hastelloy drive shaft for aggressive media such as acids and alkalies. PVDF pump tube für concentrated media. Stainless steel 316 Ti pump tubes available on demand.

Suction tube diameter at Polypropylene 25, 28 or 32 mm; at Stainless steel tubes 28 or 32 mm; at PVDF 32 mm

Standard suction tube lengths: 500, 700, 1.000 and 1.200 mm depending on the pump tube diameter (special lengths available)

Ø 25 mm: Flow rate 23 l/min, head 7 m*

Ø 28 mm: Flow rate 40 l/min, head 9 m*

Ø 32 mm: Flow rate 49 l/min, head 10 m*

Density: 1.3*

Viscosity: 400 mPas*

(with motor JP-140, 230 V, 450 W)

* All specified values are real measured maximum values. Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

BARRELPUMP.IR

JP-120 Electric universal motor


JP-140 230 Volt, 50/60 Hz, 250 or 450 Watt, IP 24, alternatively 115 Volt, 60 Hz



Description

- The drives JP-120 and JP-140 are compactly built, not explosion-proof, internally ventilated universal motors in various power classes.
- The lightweight, handy and powerful devices can be used to drive the suction tubes of the laboratory pumps and drum pumps and are suitable in this combination for many thin liquid, neutral, aggressive and non-flammable media. Their sophisticated, technically clear structure ensures an efficient and safe use when transferring different media.
- The drum pump motors are characterized not only by their lightweight (2 to 2,3 kg) but also by their elegant design and simple usage. The non-stationarily and stationarily usable drives are especially suited for intermittent operation. As internally ventilated motors, they have an optimum air cooling, low noise level and ensure high operational safety and long life time.

- The motor housing made of Polypropylene ensures high chemical resistance in case of aggressive vapours of acids and alkalis.
- The standard in the on/off switch integrated low voltage release is intended to prevent an uncontrolled start of the drum pump motor after a power failure or voltage drop and thus guarantees maximum safety. By the presence of a thermal protection, the life time of the engine is significantly increased.
- The flow rate of the transferred media can be optionally regulated via a speed control that is mounted laterally in the motor housing, be throttled and therefore adapted to the needs of the user.
- The maximum density of the media is for the JP-120 universal motor 1,2, the maximum viscosity 200 mPas. The 450 Watt motor JP-140 can be used up to a density of 1,3 and up to a viscosity of 400 mPas.



JP-120, 230 VAC, JP-PP(HC)32,28,25-1.000 test media water 20 °C, pressure pipe 1", oval gear meter, measured value ± 5%

Electric universal motor JP-120

230 Volt, 50/60 Hz, 250 Watt, IP 24, double insulation protection class II, over load protection switch with or without low voltage release. Thermal protection, 5 m cable with plug.

Speed control as option.

Operating data JP-120

Flow rate (with hose and oval gear meter): Ø 25 mm up to 20 l/min*
Ø 28 mm up to 35 l/min*
Ø 32 mm up to 40 l/min*

Head: Ø 25 mm up to 5 m*
Ø 28 mm up to 7 m*
Ø 32 mm up to 7 m*

Viscosity: up to 200 mPas*

Density: up to 1,3*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values. Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

BARRELPUMP.IR



Electric universal motor JP-140

230 Volt, 50/60 Hz, 450 Watt, IP 24, double insulation protection class II, over load protection switch with or without low voltage release. Thermal protection, 5 m cable with plug. Speed control as option.

Operating data JP-140

Flow rate (with hose and oval gear meter):
 Ø 25 mm up to 23 l/min*
 Ø 28 mm up to 40 l/min*
 Ø 32 mm up to 49 l/min*

Head:
 Ø 25 mm up to 7 m*
 Ø 28 mm up to 9 m*
 Ø 32 mm up to 10 m*

Viscosity: up to 400 mPas*
Density: up to 1,3*




JP-120	Version	Voltage	Order No.
without LVR	230 V 1~, 50/60 Hz, 250 W	1120 2300	
	115 V 1~, 60 Hz, 250 W	1120 1150	
with LVR	230 V 1~, 50/60 Hz, 250 W	1120 2301	
	115 V 1~, 60 Hz, 250 W	1120 1151	
without LVR, with SC	230 V 1~, 50/60 Hz, 250 W	1120 2302	
	115 V 1~, 60 Hz, 250 W	1120 1152	
with LVR + SC	230 V 1~, 50/60 Hz, 250 W	1120 2303	
	115 V 1~, 60 Hz, 250 W	1120 1153	

LVR: Low voltage release
 SC: Speed control



JP-140	Version	Voltage	Order No.
without LVR	230 V 1~, 50/60 Hz, 450 W	1140 2300	
	115 V 1~, 60 Hz, 450 W	1140 1150	
with LVR	230 V 1~, 50/60 Hz, 450 W	1140 2301	
	115 V 1~, 60 Hz, 450 W	1140 1151	
without LVR, with SC	230 V 1~, 50/60 Hz, 450 W	1140 2302	
	115 V 1~, 60 Hz, 450 W	1140 1152	
with LVR + SC	230 V 1~, 50/60 Hz, 450 W	1140 2303	
	115 V 1~, 60 Hz, 450 W	1140 1153	

LVR: Low voltage release
 SC: Speed control



JP-140, 230 VAC, JP-PP(HC)32,28,25-1.000, test media water 20 °C, pressure pipe oval gear meter, measure value ± 5%

Electronic speed control

The speed of the drum pump motors JP-120, JP-140 can be controlled via a knob on the side of the motor housing electronically. This enables an adjustment of the flow rate.

The electronic speed control is available as an option.



JP-AIR1 Air operated motor


300 Watt at max. 6 bar operating pressure



Description

- The drive JP-AIR 1 is a compactly built, elegant designed air motor with an Aluminium housing.
- The lightweight, handy and powerful device can be used as drive for the laboratory and drum pump tubes and is suitable in this combination for many thin liquid, neutral and aggressive media. Flammable media are not allowed to be transferred with the laboratory pump tubes made of Stainless steel cause of missing ATEX certification. The sophisticated, technically clear structure ensures an efficient and safe use when transferring various media.
- The air operated drum pump motor is characterized beside its lightweight (2 kg) by its elegant design and ease of use. The non-stationarily and stationarily usable drive is particularly suitable for intermittent operation.

- Via the included ball valve, the compressed air can be dosed at the air inlet, and thereby the rotational speed of the motor. Therefore, the flow rate of the pumped media can be adjusted to your requirements.
- The maximum operating pressure is 6 bar. The included silencer ensures a low noise level. The air consumption of the engine is under load 13 l/sec.
- The maximum density of the media for the air operated motor JP-AIR 1 is 1,3, the maximum viscosity 400 mPas.



JP-AIR1, JP-PP(HC)32,28,25-1.000, test media water 20 °C, pressure pipe 1", oval gear meter, measured values: ± 5%

Air operated motor JP-AIR 1

300 Watt at max. 6 bar operating pressure, with silencer and Brass ball valve for dosing the compressed air. Therefore, the speed of the motor and flow rate of the pump can be adjusted.

Operating data JP-AIR 1

Flow rate (with hose and oval gear meter):

- Ø 25 mm up to 18 l/min *
- Ø 28 mm up to 33 l/min *
- Ø 32 mm up to 42 l/min *

Head:

- Ø 25 mm up to 5 m *
- Ø 28 mm up to 6 m *
- Ø 32 mm up to 8 m *

Viscosity: up to 400 mPas*

Density: up to 1,3*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values. Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

► The laboratory pumps can also be combined with the air operated motors JP-AIR 2 or JP-AIR 3.



JP-AIR 1

Performance

300 W

300 Watt at max. 6 bar operating pressure

Air consumption under load 13 l/sec.

Order No.

3001 0300





BARRELPUMP.IR

Pump tubes for laboratory pumps

made of Polypropylene, Stainless steel or PVDF

Pump tubes in sealless design for pumping small quantities of neutral and lightly aggressive (with Stainless steel pump tube or Polypropylene pump tube with Stainless steel shaft) or aggressive (with Polypropylene pump tube with Hastelloy shaft or PVDF pump tube) media out of containers with narrow neck.

Pump tube made of Polypropylene, Stainless steel or PVDF, various suction tube diameters and lengths, complete with 1/2" hose connection (for PP Ø 25 mm) or 3/4" (with PP for Ø 28 and 32 mm), SS Ø 28 3/4" or SS Ø 32 1" for Stainless steel or 3/4" for PVDF Ø 32. The pump tubes can be combined with all electric motors (see page 25–32) and air operated motors (see page 37–39) outside hazardous area.

	Material of pump tube	Pump tube diameter	Pump tube length	Order No.
	Polypropylene (SS) Stainless steel drive shaft 316Ti	Ø 25 mm	500 mm	2625 0050
		Ø 25 mm	700 mm	2625 0070
		Ø 25 mm	1.000 mm	2625 0100
		Ø 28 mm	500 mm	2628 0050
		Ø 28 mm	700 mm	2628 0070
		Ø 28 mm	1.000 mm	2628 0100
		Ø 32 mm	700 mm	2632 0070
		Ø 32 mm	1.000 mm	2632 0100
		Ø 32 mm	1.200 mm	2632 0120
	Polypropylene (HC) Hastelloy drive shaft 2.4610	Ø 25 mm	500 mm	2125 0050
		Ø 25 mm	700 mm	2125 0070
		Ø 25 mm	1.000 mm	2125 0100
		Ø 28 mm	500 mm	2128 0050
		Ø 28 mm	700 mm	2128 0070
		Ø 28 mm	1.000 mm	2128 0100
		Ø 32 mm	700 mm	2132 0070
		Ø 32 mm	1.000 mm	2132 0100
		Ø 32 mm	1.200 mm	2132 0120
	Stainless steel 316Ti	Ø 28 mm	700 mm	2228 0070
		Ø 28 mm	1.000 mm	2228 0100
		Ø 28 mm	1.200 mm	2228 0120
		Ø 32 mm	700 mm	2232 0070
		Ø 32 mm	1.000 mm	2232 0100
		Ø 32 mm	1.200 mm	2232 0120
	PVDF Hastelloy drive shaft 2.4610	Ø 32 mm	500 mm	2332 0050
		Ø 32 mm	700 mm	2332 0070
		Ø 32 mm	1.000 mm	2332 0100
		Ø 32 mm	1.200 mm	2332 0120
		Ø 32 mm	1.200 mm	2332 0120

BARRELPUMP.IR

Laboratory pumps with electric motor JP-120

Laboratory pump tube made of Polypropylene with a Stainless steel drive shaft and a suction tube diameter of Ø 25 or 28 mm

For transferring and pumping small quantities of neutral or lightly aggressive media out of containers with narrow necks.

Universal motor JP-120, 230 V, 50/60 Hz, 250 W, IP 24, alternatively 115 V, 60 Hz, double insulated protection class II, on/off switch, thermal protection, 5 m cable with plug.



Material of Pump tube	Motor version	Pump tube diameter	Pump tube length	Order No.	
LVR: Low voltage release, SC: Speed control					
JP-125 Polypropylene (SS) Stainless steel drive shaft 316Ti	without LVR	Ø 25 mm	500 mm	1625 0050	
	with LVR	Ø 25 mm	500 mm	1625 0051	
	without LVR, with SC	Ø 25 mm	500 mm	1625 0052	
	with LVR + SC	Ø 25 mm	500 mm	1625 0053	
	without LVR	Ø 25 mm	700 mm	1625 0070	
	with LVR	Ø 25 mm	700 mm	1625 0071	
	without LVR, with SC	Ø 25 mm	700 mm	1625 0072	
	with LVR + SC	Ø 25 mm	700 mm	1625 0073	
	without LVR	Ø 25 mm	1.000 mm	1625 0100	
	with LVR	Ø 25 mm	1.000 mm	1625 0101	
	without LVR, with SC	Ø 25 mm	1.000 mm	1625 0102	
	with LVR + SC	Ø 25 mm	1.000 mm	1625 0103	
	JP-128 Polypropylene (SS) Stainless steel drive shaft 316Ti	without LVR	Ø 28 mm	500 mm	1628 0050
		with LVR	Ø 28 mm	500 mm	1628 0051
		without LVR, with SC	Ø 28 mm	500 mm	1628 0052
		with LVR + SC	Ø 28 mm	500 mm	1628 0053
without LVR		Ø 28 mm	700 mm	1628 0070	
with LVR		Ø 28 mm	700 mm	1628 0071	
without LVR, with SC		Ø 28 mm	700 mm	1628 0072	
with LVR + SC		Ø 28 mm	700 mm	1628 0073	
without LVR		Ø 28 mm	1.000 mm	1628 0100	
with LVR		Ø 28 mm	1.000 mm	1628 0101	
without LVR, with SC		Ø 28 mm	1.000 mm	1628 0102	
with LVR + SC		Ø 28 mm	1.000 mm	1628 0103	

Hose connection included in delivery:

For pump tube made of PP with Ø 25 mm: hose connection 1/2"
 for pump tube made of PP with Ø 28 mm: hose connection 3/4"

BARRELPUMP.IR

Laboratory pumps with electric motor JP-120

Laboratory pump tube made of Polypropylene with a Hastelloy drive shaft and a suction tube diameter of Ø 25 or 28 mm

For transferring and pumping small quantities of acids and alkaline media out of containers with narrow necks.

Universal motor JP-120, 230 V, 50/60 Hz, 250 W, IP 24, alternatively 115 V, 60 Hz, double insulated protection class II, on/off switch, thermal protection, 5 m cable with plug.



Material of Pump tube	Motor version	Pump tube diameter	Pump tube length	Order No.	
JP-125 Polypropylene (HC) Hastelloy drive shaft 2.4610	LVR: Low voltage release, SC: Speed control				
	without LVR	Ø 25 mm	500 mm	1125 0050	
	with LVR	Ø 25 mm	500 mm	1125 0051	
	without LVR, with SC	Ø 25 mm	500 mm	1125 0052	
	with LVR + SC	Ø 25 mm	500 mm	1125 0053	
	without LVR	Ø 25 mm	700 mm	1125 0070	
	with LVR	Ø 25 mm	700 mm	1125 0071	
	without LVR, with SC	Ø 25 mm	700 mm	1125 0072	
	with LVR + SC	Ø 25 mm	700 mm	1125 0073	
	without LVR	Ø 25 mm	1.000 mm	1125 0100	
	with LVR	Ø 25 mm	1.000 mm	1125 0101	
	without LVR, with SC	Ø 25 mm	1.000 mm	1125 0102	
	with LVR + SC	Ø 25 mm	1.000 mm	1125 0103	
	JP-128 Polypropylene (HC) Hastelloy drive shaft 2.4610	without LVR	Ø 28 mm	500 mm	1128 0050
		with LVR	Ø 28 mm	500 mm	1128 0051
		without LVR, with SC	Ø 28 mm	500 mm	1128 0052
with LVR + SC		Ø 28 mm	500 mm	1128 0053	
without LVR		Ø 28 mm	700 mm	1128 0070	
with LVR		Ø 28 mm	700 mm	1128 0071	
without LVR, with SC		Ø 28 mm	700 mm	1128 0072	
with LVR + SC		Ø 28 mm	700 mm	1128 0073	
without LVR		Ø 28 mm	1.000 mm	1128 0100	
with LVR		Ø 28 mm	1.000 mm	1128 0101	
without LVR, with SC		Ø 28 mm	1.000 mm	1128 0102	
with LVR + SC		Ø 28 mm	1.000 mm	1128 0103	

Hose connection included in delivery:

For pump tube made of PP with Ø 25 mm: hose connection 1/2"
 for pump tube made of PP with Ø 28 mm: hose connection 3/4"


BARRELPUMP.IR

Laboratory pumps with electric motor JP-120

Laboratory pump tube made of Stainless steel
with a suction tube diameter of Ø 28 mm

For transferring and pumping small quantities of neutral or lightly aggressive media out of containers with narrow necks.

Universal motor JP-120, 230 V, 50/60 Hz, 250 W, IP 24, alternatively 115 V, 60 Hz, double insulated protection class II, on/off switch, thermal protection, 5 m cable with plug.

	Material of Pump tube	Motor version	Pump tube diameter	Pump tube length	Order No.
	JP-128 Stainless steel 316Ti	LVR: Low voltage release, SC: Speed control			
		without LVR	Ø 28 mm	700 mm	1228 0070
		with LVR	Ø 28 mm	700 mm	1228 0071
		without LVR, with SC	Ø 28 mm	700 mm	1228 0072
		with LVR + SC	Ø 28 mm	700 mm	1228 0073
		without LVR	Ø 28 mm	1.000 mm	1228 0100
		with LVR	Ø 28 mm	1.000 mm	1228 0101
		without LVR, with SC	Ø 28 mm	1.000 mm	1228 0102
		with LVR + SC	Ø 28 mm	1.000 mm	1228 0103
		without LVR	Ø 28 mm	1.200 mm	1228 0120
		with LVR	Ø 28 mm	1.200 mm	1228 0121
		without LVR, with SC	Ø 28 mm	1.200 mm	1228 0122
with LVR + SC	Ø 28 mm	1.200 mm	1228 0123		

Hose connection included in delivery:

For SS pump tube with Ø 28 mm: hose connection 3/4".

BARRELPUMP.IR

Laboratory pumps with electric motor JP-140

Laboratory pump tube made of Polypropylene with a Stainless steel or Hastelloy drive shaft and a suction tube diameter of Ø 32 mm

For transferring and pumping small quantities of neutral or lightly aggressive media out of containers with narrow necks.

Universal motor JP-140, 230 V, 50/60 Hz, 450 W, IP 24, alternatively 115 V, 60 Hz, double insulated protection class II, on/off switch, thermal protection, 5 m cable with plug.



Material of Pump tube	Motor version	Pump tube diameter	Pump tube length	Order No.	
LVR: Low voltage release, SC: Speed control					
JP-132 Polypropylene (SS) Stainless steel drive shaft 316Ti	without LVR	Ø 32 mm	700 mm	1632 0070	
	with LVR	Ø 32 mm	700 mm	1632 0071	
	without LVR, with SC	Ø 32 mm	700 mm	1632 0072	
	with LVR + SC	Ø 32 mm	700 mm	1632 0073	
	without LVR	Ø 32 mm	1.000 mm	1632 0100	
	with LVR	Ø 32 mm	1.000 mm	1632 0101	
	without LVR, with SC	Ø 32 mm	1.000 mm	1632 0102	
	with LVR + SC	Ø 32 mm	1.000 mm	1632 0103	
	without LVR	Ø 32 mm	1.200 mm	1632 0120	
	with LVR	Ø 32 mm	1.200 mm	1632 0121	
	without LVR, with SC	Ø 32 mm	1.200 mm	1632 0122	
	with LVR + SC	Ø 32 mm	1.200 mm	1632 0123	
	JP-132 Polypropylene (HC) Hastelloy drive shaft 2.4610	without LVR	Ø 32 mm	700 mm	1132 0070
		with LVR	Ø 32 mm	700 mm	1132 0071
		without LVR, with SC	Ø 32 mm	700 mm	1132 0072
		with LVR + SC	Ø 32 mm	700 mm	1132 0073
without LVR		Ø 32 mm	1.000 mm	1132 0100	
with LVR		Ø 32 mm	1.000 mm	1132 0101	
without LVR, with SC		Ø 32 mm	1.000 mm	1132 0102	
with LVR + SC		Ø 32 mm	1.000 mm	1132 0103	
without LVR		Ø 32 mm	1.200 mm	1132 0120	
with LVR		Ø 32 mm	1.200 mm	1132 0121	
without LVR, with SC		Ø 32 mm	1.200 mm	1132 0122	
with LVR + SC		Ø 32 mm	1.200 mm	1132 0123	

Hose connection included in delivery:

For pump tube made of PP with Ø 32 mm: hose connection 3/4"


BARRELPUMP.IR

Laboratory pumps with electric motor JP-140

Laboratory pump tube made of Stainless steel or PVDF and a suction tube diameter of Ø 32 mm


For transferring and pumping small quantities of neutral or lightly aggressive media out of containers with narrow necks.

Universal motor JP-140, 230 V, 50/60 Hz, 450 W, IP 24, alternatively 115 V, 60 Hz, double insulated protection class II, on/off switch, thermal protection, 5 m cable with plug.

	Material of Pump tube	Motor version	Pump tube diameter	Pump tube length	Order No.
	JP-132 Stainless steel 316Ti	LVR: Low voltage release, SC: Speed control			
		without LVR	Ø 32 mm	700 mm	1232 0070
		with LVR	Ø 32 mm	700 mm	1232 0071
		without LVR, with SC	Ø 32 mm	700 mm	1232 0072
		with LVR + SC	Ø 32 mm	700 mm	1232 0073
		without LVR	Ø 32 mm	1.000 mm	1232 0100
		with LVR	Ø 32 mm	1.000 mm	1232 0101
		without LVR, with SC	Ø 32 mm	1.000 mm	1232 0102
		with LVR + SC	Ø 32 mm	1.000 mm	1232 0103
		without LVR	Ø 32 mm	1.200 mm	1232 0120
		with LVR	Ø 32 mm	1.200 mm	1232 0121
		without LVR, with SC	Ø 32 mm	1.200 mm	1232 0122
		with LVR + SC	Ø 32 mm	1.200 mm	1232 0123

For transferring and pumping small quantities of highly aggressive media out of containers with narrow necks.

Universal motor JP-140, 230 V, 50/60 Hz, 450 W, IP 24, alternatively 115 V, 60 Hz, double insulated protection class II, on/off switch, thermal protection, 5 m cable with plug.

	Material of Pump tube	Motor version	Pump tube diameter	Pump tube length	Order No.
	JP-132 PVDF Hastelloy drive shaft 2.4610	LVR: Low voltage release			
		with LVR	Ø 32 mm	500 mm	1332 0051
		with LVR	Ø 32 mm	700 mm	1332 0071
		with LVR	Ø 32 mm	1.000 mm	1332 0101
		with LVR	Ø 32 mm	1.200 mm	1332 0121

BARRELPUMP.IR

Hose connection included in delivery:

For SS pump tube with Ø 32 mm: hose connection 1".

For PVDF pump tube with Ø 32 mm: hose connection ¾".




Laboratory pumps with air operated motor JP-AIR 1

Laboratory pump tube made of Polypropylene or Stainless steel and with a suction tube diameter of Ø 25, 28 and 32 mm

Modular system:
 Motors JP-AIR 2 and JP-AIR 3 are also useable

For transferring and pumping small quantities of neutral and lightly aggressive (with Stainless steel pump tube or Polypropylene pump tube with Stainless steel shaft) or aggressive (with Polypropylene pump tube and Hastelloy drive shaft) media out of containers with narrow necks.

Air operated motor JP-AIR 1, 300 W at max. 6 bar, with ball valve and silencer, air consumption under load 13 l/sec.

	Material of pump tube	Pump tube diameter	Pump tube length	Order No.	
	Polypropylene (SS) Stainless steel drive shaft 316Ti	JP-325	Ø 25 mm	500 mm	3625 0050
			Ø 25 mm	700 mm	3625 0070
			Ø 25 mm	1.000 mm	3625 0100
		JP-328	Ø 28 mm	500 mm	3628 0050
			Ø 28 mm	700 mm	3628 0070
			Ø 28 mm	1.000 mm	3628 0100
		JP-332	Ø 32 mm	700 mm	3632 0070
			Ø 32 mm	1.000 mm	3632 0100
			Ø 32 mm	1.200 mm	3632 0120
	Polypropylene (HC) Hastelloy drive shaft 2.4610	JP-325	Ø 25 mm	500 mm	3125 0050
			Ø 25 mm	700 mm	3125 0070
			Ø 25 mm	1.000 mm	3125 0100
		JP-328	Ø 28 mm	500 mm	3128 0050
			Ø 28 mm	700 mm	3128 0070
			Ø 28 mm	1.000 mm	3128 0100
		JP-332	Ø 32 mm	700 mm	3132 0070
			Ø 32 mm	1.000 mm	3132 0100
			Ø 32 mm	1.200 mm	3132 0120
	Stainless steel 316Ti	JP-328	Ø 28 mm	700 mm	3228 0070
			Ø 28 mm	1.000 mm	3228 0100
			Ø 28 mm	1.200 mm	3228 0120
		JP-332	Ø 32 mm	700 mm	3232 0070
			Ø 32 mm	1.000 mm	3232 0100
			Ø 32 mm	1.200 mm	3232 0120

BARRELPUMP.IR

Hose connection included in delivery:

For pump tube made of PP with Ø 25 mm: hose connection ½",
 for pump tube made of PP with Ø 28 and 32 mm: hose connection ¾".

For SS pump tube with Ø 28 mm: hose connection ¾",
 for SS pump tube with Ø 32 mm: hose connection 1".

Accessories for laboratory pumps

		Order No.	
	<p>Nozzle made of Polypropylene for a safe filling and transferring of low quantities with hose connection 1/2" (NW 13).</p>	1/2"	9016
	<p>Nozzle made of Polypropylene Housing and internal parts made of Polypropylene, valve seat and O-rings made of FKM or EPDM, rotatable hose connection. Flow rate: 80 l/min* Viscosity: 800 mPas Operating pressure: 3 bar* Weight: 210 g</p>	1/2"	9101
		3/4"	9102
	<p>Barrel adapter made of Polypropylene for secure fixing of drum pump in bung-hole of a drum Diameter of pump tube 25, 28 or 32 mm, G 2".</p>	Ø 25	9078
		Ø 28	9079
		Ø 32	9080
	<p>Barrel adapter made of Stainless steel for secure fixing of drum pump in bung-hole of a drum Diameter of pump tube 32 mm, G 2".</p>	Ø 32	9081
<p>The barrel adapters fit due to their 2" thread in 60 and 200 liter steel drums. For use in plastic drums or plastic canisters they can be combined with the thread adapters on page 10.</p>			
	<p>Wall hanger for laboratory pump for a secure storage of barrel pump when out of operation and for protection against damages.</p>		9007
	<p>PVC-hose crystal clear with fabric lining, suitable for non flammable, neutral and aggressive media. Operating pressure: 10 bar* Temperature: -35 °C up to +60 °C*</p>	1/2"	9049
		3/4"	9050
	<p>Universal chemical- and solvent hose, conductive inner wall homogeneous, smooth, EPDM (Ethylene Propylene Rubber) conductive, suitable for many alkalis, acids, acetates, aldehydes, amines, esters, ethers and ketones, not suitable for carbonic gassy products and their derivatives, as well as oils and gasoline. Operating pressure: 16 bar* Temperature: -40 °C up to +90 °C*</p>	1/2"	9054
		3/4"	9055
	<p>Multi purpose chemical hose, conductive inner wall homogeneous, smooth, PE-X (knitted Polyethylene), conductive, suitable for nearly all chemicals. Not suitable for oleum, brom and chlorsulfon acid Operating pressure: 10 bar* Temperature: -25 °C up to +90 °C*</p>	1/2"	9059
		3/4"	9060

BARRELPUMP.IR

Laboratory pump sets

Laboratory pump sets JP-120/JP-140

Order No.



Laboratory pump set JP-120 PP (HC) 700, Ø 28 mm

Universal motor JP-120, 230 Volt, 50/60 Hz, 250 Watt, IP 24 internally ventilated universal motor, splash protection to IP 24, thermal protection, on/off switch, 5 m cable with plug, double isolated class II, over load protection switch with low voltage release

Pump tube: Polypropylene, sealless, 700 mm, outer-Ø 28 mm, HC-shaft 2.4610, connection thread G 1", hose connection 3/4" (NW 19)

2 m PVC hose 3/4" (NW 19)

2 Hose clamps Stainless steel

1 Nozzle Polypropylene FKM 3/4"

Flow rate: up to 35 l/min*, **Head:** up to 7 m*, **Density:** up to 1.2*

Medium temperature: up to 50 °C, **Viscosity:** up to 200 mPas*

1121 2807



Laboratory pump set JP-120 PP (HC) 1000, Ø 28 mm

Universal motor JP-120, 230 Volt, 50/60 Hz, 250 Watt, IP 24 internally ventilated universal motor, splash protection to IP 24, thermal protection, on/off switch, 5 m cable with plug, double isolated class II, over load protection switch with low voltage release

Pump tube: Polypropylene, sealless, 1.000 mm, outer-Ø 28 mm, HC-shaft 2.4610, connection thread G 1", hose connection 3/4" (NW 19)

2 m PVC hose 3/4" (NW 19)

2 Hose clamps Stainless steel

1 Nozzle Polypropylene FKM 3/4"

Flow rate: up to 35 l/min*, **Head:** up to 7 m*, **Density:** up to 1.2*

Medium temperature: up to 50 °C, **Viscosity:** up to 200 mPas*

1121 2810

Laboratory pump set JP-140 SS 1000, Ø 32 mm

Universal motor JP-140, 230 Volt, 50/60 Hz, 450 Watt, IP 24 internally ventilated universal motor, splash protection to IP 24, thermal protection, on/off switch, 5 m cable with plug, double isolated class II, over load protection switch with low voltage release

Pump tube: Stainless steel 316Ti, sealless, 1.000 mm, outer-Ø 32 mm, connection thread G 1", hose connection 3/4" (NW 19)

2 m Universal chemical hose 3/4" (NW 19)

2 Hose clamps Stainless steel

1 Nozzle Brass nickel plated 3/4"

Flow rate: up to 49 l/min*, **Head:** up to 10 m*, **Density:** up to 1.3*

Medium temperature: up to 90 °C, **Viscosity:** up to 400 mPas*

1141 3210

Laboratory pump set JP-AIR 1



Laboratory pump set JP-AIR 1 SS 1000, Ø 32 mm

Air operated motor JP-AIR 1, 300 W at max. 6 bar operating pressure. Motor with Brass ball valve and muffler for compressed air control. This regulates the motor speed and varies the pumping capacity.

Pump tube: Stainless steel 316Ti, sealless, 1.000 mm, outer-Ø 32 mm, connection thread G 1", hose connection 3/4" (NW 19)

2 m Universal chemical hose 3/4" (NW 19)

2 Hose clamps Stainless steel

1 Nozzle Brass nickel plated 3/4"

Flow rate: up to 42 l/min*, **Head:** up to 8 m*, **Density:** up to 1.3*

Medium temperature: up to 90 °C, **Viscosity:** up to 400 mPas*

3012 3210

* All specified values are real measured maximum values.

* Test medium water 20 °C, pressure pipe 1",

oval gear meter 1", measured values: ± 5%

Attention: When using a nozzle, the flow rate is reduced to app. 20-40 l/min (depends on the pump and application).

BARRELPUMP-IR

Drum and container pumps

for pumping thin fluid media such as acids, alkalis and detergents (with Polypropylene pump tube), highly aggressive chemicals (with PVDF pump tube), mineral oil products up to 1.000 mPas (with Aluminium pump tube) or flammable media and food (with Stainless steel 316Ti pump tube)



Electric motor

Pump tube

► The flow rate of a drum pump depends initially on the speed of the motor and then on motor power.

► For flammable media and for use in hazardous environments explosion proof drum pumps with accessories are available. The electric and air operated engines and pump tubes of conductive Stainless steel need an ATEX approval. When pumping flammable media a potential equalization is mandatory.

The particular advantages in an overview:

- The JESSBERGER universal motors that can be combined with all pump tubes on pages 40 to 45 outside hazardous areas are lightweight, handy and powerful devices for nearly all thin fluid and lightly viscous media.
- The non-stationarily and stationarily applicable drum pump motors are particularly suitable for intermittent operation.
- The sophisticated, technically clear structure of the drum pump ensures a rational and safe use.
- Quick disconnection of the drive from the pump tube through a few rotations enables the combination of an engine with various pump tubes for different media.

- Wide range of accessories such as drum and threaded adapters, media-resistant hoses, nozzles, wall hanger or flow meter is available on request (see page 46 et seq.).
- Easy disassembling and quick cleaning of the pump tubes.



Axial (rotor)
For higher flow rates

Radial (impeller)
For larger heads

Air operated motor



Pump tube

Media depending on pump tube

Pump tube made of Polypropylene:
For aggressive media such as acids, alkalis and detergents. Maximum temperature 50 °C.

Pump tube made of PVDF:
For highly aggressive media such as chlorine bleach, chromic acid, hydrofluoric acid, nitric acid, sulfuric acid > 90%. Maximum temperature 90 °C.

Pump tube made of Aluminium:
For mineral oil products such as diesel, heating oil, hydraulic oils, gear oils, engine oils, mineral oils and motor oils up to 1.000 mPas.

Pump tube made of Stainless steel:
For neutral, lightly aggressive media and specifically for lightly flammable media and food.

For more details see the introduction on page 5.
Please ask us regarding the chemical resistance.

Electronic speed control

The speed of the drum pump motors can be controlled electronically via a knob on the handle. This enables an adjustment of the flow rate.
The electronic speed control is available as an option.

BARRELPUMP.IR

JP-120 Electric universal motor


230 Volt, 50/60 Hz, 250 Watt, IP 24, alternatively 115 Volt, 60 Hz



Description

- The drive JP-120 is a compactly built, not explosion-proof, internally ventilated universal motor.
- The lightweight, handy and powerful device can be used as drive for the pump tubes of the laboratory and drum pumps and is useful in this combination for many thin fluid, neutral, aggressive and non-flammable media. Its sophisticated, technically clear structure ensures an efficient and safe use when transferring a variety of water-like liquids.
- The drum pump motor is characterized not only by its lightweight (2 kg) but also by its elegant design and ease of use. The non-stationarily and stationarily usable drive is particularly suitable for intermittent operation. As internally ventilated motor, it has an optimal air cooling, low noise level and ensures high operational safety and long time life.

- The motor housing made of Polypropylene ensures high chemical resistance in case of aggressive vapours of acids and alkalis.
- The standard in the on/off switch integrated low voltage release is intended to prevent an uncontrolled start of the drum pump motor after a power failure or voltage drop and thus guarantees maximum safety. By the presence of a thermal protection the life of the engine is significantly increased.
- The flow rate of the media that will be pumped can be adjusted by the optionally available speed control that is mounted laterally in the motor housing and therefore adapted to the needs of the user.
- The maximum density of the media is for the JP-120 universal motor 1,2, the maximum viscosity 200 mPas.



JP-120, 230 VAC, JP-PP(HC)41-1.000, test media water 20 °C, pressure pipe 1", oval gear meter, measured values: ± 5%

Electric universal motor JP-120

230 Volt, 50/60 Hz, 250 Watt, IP 24, double insulation protection class II, over load protection switch with integrated low voltage release. Thermal protection, 5 m cable with plug.

Speed control as option.

Operating data JP-120

Flow rate (with hose and oval gear meter):	up to 71 l/min (Rotor)* up to 55 l/min (Impeller)*
Head:	up to 7 m (Rotor)* up to 16 m (Impeller)*
Viscosity:	up to 200 mPas*
Density:	up to 1,2*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values. Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

JP-120




Version	Voltage	Order No.
without LVR	230 V 1~, 50/60 Hz, 250 W	1120 2300
	115 V 1~, 60 Hz, 250 W	1120 1150
with LVR	230 V 1~, 50/60 Hz, 250 W	1120 2301
	115 V 1~, 60 Hz, 250 W	1120 1151
without LVR, with SC	230 V 1~, 50/60 Hz, 250 W	1120 2302
	115 V 1~, 60 Hz, 250 W	1120 1152
with LVR + SC	230 V 1~, 50/60 Hz, 250 W	1120 2303
	115 V 1~, 60 Hz, 250 W	1120 1153

LVR: Low voltage release
SC: Speed control

Electronic speed control

The speed of the drum pump motor JP-120 can be controlled via a knob on the side of the motor housing electronically. This enables an adjustment of the flow rate. The electronic speed control is available as an option.



JP-140 Electric universal motor


230 Volt, 50/60 Hz, 450 Watt, IP 24, alternatively 115 Volt, 60 Hz



Description

- The drive JP-140 is a compactly built, not explosion-proof, internally ventilated universal motor.
- The lightweight, handy and powerful device can be used as drive for the pump tubes of the laboratory and drum pumps and is useful in this combination for many thin fluid, neutral, aggressive and non-flammable media. Its sophisticated, technically clear structure ensures an efficient and safe use when transferring a variety of water-like liquids.
- The drum pump motor is characterized not only by its lightweight (2,3 kg) but also by its elegant design and ease of use. The non-stationarily and stationarily usable drive is particularly suitable for intermittent operation. As internally ventilated motor it has an optimal air cooling, low noise level and ensures high operational safety and long lifetime.

- The motor housing made of Polypropylene ensures high chemical resistance in case of aggressive vapours of acids and alkalis.
- The standard in the on/off switch integrated low voltage release is intended to prevent an uncontrolled start of the drum pump motor after a power failure or voltage drop and thus guarantees maximum safety. By the presence of a thermal protection the life of the engine is significantly increased.
- The flow rate of the media that will be pumped can be adjusted by the optionally available speed control that is mounted laterally in the motor housing and therefore adapted to the needs of the user.
- The maximum density of the media is for the JP-140 universal motor 1,3, the maximum viscosity 400 mPas.



JP-140, 230 VAC, JP-PP(HC)41-1.000, test media water 20 °C, pressure pipe 1", oval gear meter, measured values: ± 5%

Electric universal motor JP-140

230 Volt, 50/60 Hz, 450 Watt, IP 24, double insulation protection class II, over load protection switch with integrated low voltage release. Thermal protection, 5 m cable with plug.

Speed control as option.

Operating data JP-140

Flow rate (with hose and oval gear meter):	up to 87 l/min (Rotor)* up to 70 l/min (Impeller)*
Head:	up to 10 m (Rotor)* up to 23 m (Impeller)*
Viscosity:	up to 400 mPas*
Density:	up to 1,3*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values. Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

JP-140




Version	Voltage	Order No.
without LVR	230 V 1~, 50/60 Hz, 450 W	1140 2300
	115 V 1~, 60 Hz, 450 W	1140 1150
with LVR	230 V 1~, 50/60 Hz, 450 W	1140 2301
	115 V 1~, 60 Hz, 450 W	1140 1151
without LVR, with SC	230 V 1~, 50/60 Hz, 450 W	1140 2302
	115 V 1~, 60 Hz, 450 W	1140 1152
with LVR + SC	230 V 1~, 50/60 Hz, 450 W	1140 2303
	115 V 1~, 60 Hz, 450 W	1140 1153

LVR: Low voltage release
SC: Speed control

Electronic speed control

The speed of the drum pump motor JP-140 can be controlled via a knob on the side of the motor housing electronically. This enables an adjustment of the flow rate. The electronic speed control is available as an option.




JP-160 Electric universal motor

230 Volt, 50/60 Hz, 460 Watt, IP 24

Description

- The drive JP-160 is a compactly built, not explosion-proof, internally ventilated universal motor that has proven itself in very large numbers for low viscous media such as the urea solution AdBlue.
- This handy, very robust and powerful motor can be used to drive the suction tubes of drum pumps. In this combination it is suitable for many thin fluid and lightly viscous, neutral, aggressive and non-flammable liquids (max. 400 mPas). Its sophisticated, technically clear structure ensures an efficient and safe use when transferring a wide range of media.
- The drum pump motor is characterized not only by its lightweight (2,9 kg) but also by its elegant design and ease of use. The non-stationarily and stationarily usable drive is particularly suitable for intermittent operation. As internally ventilated motor it has an optimal air cooling, low noise and ensures high operational safety and long lifetime.

- The motor housing made of Polypropylene ensures high chemical resistance in case of aggressive vapours of acids and alkalis.
- The standard in the on/off switch integrated low voltage release is intended to prevent an uncontrolled start of the drum pump motor after a power failure or voltage drop and thus guarantees maximum safety.
- The flow rate of the media to be pumped can be regulated by an optionally available speed control that is integrated in the motor handle. Therefore the flow rate can be adjusted to the needs of the user.
- The maximum density of the media is for the JP-160 universal motor 1,3, the maximum viscosity 400 mPas.



Electric universal motor JP-160

230 Volt, 50/60 Hz, 460 Watt, IP 24, double insulation protection class II, over load protection switch with integrated low voltage release. 5 m cable with plug.

Speed control as option.

Operating data JP-160

Flow rate (with hose and oval gear meter): up to 82 l/min (Rotor)*
 up to 61 l/min (Impeller)*

Head: up to 9 m (Rotor)*
 up to 20 m (Impeller)*

Viscosity: up to 400 mPas*

Density: up to 1,3*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values.
 Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

JP-160

Version	Voltage	Order No.
without LVR	230 V 1~, 50/60 Hz, 460 W	1160 2300
with LVR	230 V 1~, 50/60 Hz, 460 W	1160 2301
without LVR, with SC	230 V 1~, 50/60 Hz, 460 W	1160 2302
with LVR + SC	230 V 1~, 50/60 Hz, 460 W	1160 2303

LVR: Low voltage release
 SC: Speed control



Electronic speed control

The speed of the drum pump motor JP-160 can be controlled electronically via a knob on the handle. This enables an adjustment of the flow rate.

The electronic speed control is available as an option.



JP-164 Electric universal motor


24 Volt, DC, 400 Watt, IP 24

Description

- The drum pump motor JP-164 is a compactly built, not explosion-proof, internally ventilated universal motor, that has proven itself for lightly viscous media as diesel in agricultural field and at fire brigades foaming agents.
- This handy, very robust and powerful engine can be used as a 24 Volt engine for the suction tubes of drum pumps and is in this combination suitable for many thin fluid and lightly viscous, neutral, aggressive and non-flammable liquids (max. 300 mPas). Its sophisticated, technically clear structure ensures an efficient and safe use when transferring a wide range of media.
- The drum pump motor is characterized not only by its lightweight (2,9 kg) but also by its elegant design and ease of use. The non-stationarily and stationarily usable drive is particularly suitable for intermittent operation.

As internally ventilated motor it has an optimal air cooling, low noise and ensures high operational safety and long lifetime.

- An overload circuit breaker prevents overloading of the drum pump motor.
- The motor is supplied at the end of the 5 meter cable as standard with two battery poles. For use by firefighters, police or army a 2-pole plug in screw connection according to DIN 14690 can be mounted alternatively.
- The motor housing made of Polypropylene ensures high chemical resistance in case of aggressive vapours of acids and alkalis.
- The maximum density of the media is for the JP-164 universal motor 1,3, the maximum viscosity 300 mPas.



JP-164, 24VDC, max. 15A, JP-PP(HC)41-1.000, test media water 20 °C, pressure pipe 1", oval gear meter, measured values: ± 5%

Electric universal motor JP-164

24 volts DC, 400 Watt, IP 24, double insulated protection class II, overload protection, 5 m cable with battery clamps.

Operating data JP-164

Flow rate (with hose and oval gear meter):	up to 66 l/min (Rotor)* up to 55 l/min (Impeller)*
Head:	up to 7,5 m (Rotor)* up to 15 m (Impeller)*
Viscosity:	up to 300 mPas*
Density:	up to 1,3*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values. Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

JP-164	Voltage	Order No.
	24 V DC, 400 W	1164 0240

BARRELPUMP.IR



JP-180 Electric universal motor


230 Volt, 50/60 Hz, 640 Watt, IP 24, alternatively 115 Volt, 60 Hz

Description

- The drive JP-180 is a compactly built, not explosion-proof, internally ventilated universal motor that is our top seller for aggressive media in the chemical and the galvanic industry beside JP-280.
- This handy, very robust and powerful motor can be used to drive the suction tubes of drum pumps. In this combination it is suitable for many thin liquid and lightly viscous, neutral, aggressive and non-flammable liquids (max. 600 mPas). Its sophisticated, technically clear structure ensures an efficient and safe use when transferring a wide range of media.
- The drum pump motor is characterized not only by its lightweight (3,6 kg) but also by its elegant design and ease of use. The non-stationarily and stationarily usable drive is particularly suitable for intermittent operation. As internally ventilated motor it has an optimal air

cooling, low noise and ensures high operational safety and long lifetime.

- The motor housing made of Polypropylene ensures high chemical resistance in case of aggressive vapours of acids and alkalies.
- The standard in the on/off switch integrated low voltage release is intended to prevent an uncontrolled start of the drum pump motor after a power failure or voltage drop and thus guarantees maximum safety.
- The flow rate of the media to be pumped can be regulated by an optionally available speed control that is integrated in the motor handle. Therefore the flow rate can be adjusted to the needs of the user.
- The maximum density of the media is for the JP-180 universal motor 1,5, the maximum viscosity 600 mPas.



JP-180, 230 VAC, JP-PP(HC)41-1.000, test media water 20 °C, pressure pipe 1", oval gear meter, measured values: ± 5%

Electric universal motor JP-180

230 Volt, 50/60 Hz, 640 Watt, IP 24, double insulation protection class II, over load protection switch with integrated low voltage release. 5 m cable with plug. Speed control as option.

Operating data JP-180

Flow rate (with hose and oval gear meter):	up to 93 l/min (Rotor)* up to 74 l/min (Impeller)*
Head:	up to 11 m (Rotor)* up to 26 m (Impeller)*
Viscosity:	up to 600 mPas*
Density:	up to 1,5*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values. Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

JP-180

Version	Voltage	Order No.
without LVR	230 V 1~, 50/60 Hz, 640 W	1180 2300
	115 V 1~, 60 Hz, 640 W	1180 1150
with LVR	230 V 1~, 50/60 Hz, 640 W	1180 2301
	115 V 1~, 60 Hz, 640 W	1180 1151
without LVR, with SC	230 V 1~, 50/60 Hz, 640 W	1180 2302
	115 V 1~, 60 Hz, 640 W	1180 1152
with LVR + SC	230 V 1~, 50/60 Hz, 640 W	1180 2303
	115 V 1~, 60 Hz, 640 W	1180 1153

LVR: Low voltage release
SC: Speed control



Electronic speed control

The speed of the drum pump motor JP-180 can be controlled electronically via a knob on the handle. This enables an adjustment of the flow rate.

The electronic speed control is available as an option.

JP-280 Electric universal motor

230 Volt, 50/60 Hz, 825 Watt, IP 24, alternatively 115 Volt, 60 Hz




Description

- The drive JP-280 is a compactly built, not explosion-proof, internally ventilated universal motor that is our top seller for aggressive media in the chemical and the galvanic industry beside JP-180.
- This handy, very robust and powerful motor can be used to drive the suction tubes of drum pumps. In this combination it is suitable for many thin liquid and lightly viscous, neutral, aggressive and non-flammable liquids (max 1.000 mPas). Its sophisticated, technically clear structure ensures an efficient and safe use when transferring a wide range of media.
- The drum pump motor is characterized not only by its lightweight (3,8 kg) but also by its elegant design and ease of use. The non-stationarily and stationarily usable drive is particularly suitable for intermittent operation. As internally

ventilated motor it has an optimal air cooling, low noise and ensures high operational safety and long lifetime.

- The motor housing made of Polypropylene ensures high chemical resistance in case of aggressive vapours of acids and alkalis.
- The standard in the on/off switch integrated low voltage release is intended to prevent an uncontrolled start of the drum pump motor after a power failure or voltage drop and thus guarantees maximum safety.
- The flow rate of the media to be pumped can be regulated by an optionally available speed control that is integrated in the motor handle. Therefore the flow rate can be adjusted to the needs of the user.
- The maximum density of the media is for the JP-280 universal motor 1,9, the maximum viscosity 1.000 mPas.



Electric universal motor JP-280

230 Volt, 50/60 Hz, 825 Watt, IP 24, double insulation protection class II, over load protection switch with integrated low voltage release. 5 m cable with plug.

Speed control as option.

Operating data JP-280

Flow rate (with hose and oval gear meter):	up to 112 l/min (Rotor)* up to 83 l/min (Impeller)*
Head:	up to 16 m (Rotor)* up to 37 m (Impeller)*
Viscosity:	up to 1.000 mPas*
Density:	up to 1,9*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values. Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

JP-280

Version	Voltage	Order No.
without LVR	230 V 1~, 50/60 Hz, 825 W	1280 2300
	115 V 1~, 60 Hz, 825 W	1280 1150
with LVR	230 V 1~, 50/60 Hz, 825 W	1280 2301
	115 V 1~, 60 Hz, 825 W	1280 1151
without LVR, with SC	230 V 1~, 50/60 Hz, 825 W	1280 2302
	115 V 1~, 60 Hz, 825 W	1280 1152
with LVR + SC	230 V 1~, 50/60 Hz, 825 W	1280 2303
	115 V 1~, 60 Hz, 825 W	1280 1153

LVR: Low voltage release
SC: Speed control

Electronic speed control


The speed of the drum pump motor JP-280 can be controlled electronically via a knob on the handle. This enables an adjustment of the flow rate.

The electronic speed control is available as an option.




JP-360 Electric universal motor

230 Volt, 50/60 Hz, 640 Watt, IP 55



Description

- The drive JP-360 is a compactly built, not explosion-proof, externally ventilated universal motor.
- This handy, very robust and powerful motor can be used to drive the suction tubes of drum pumps. In this combination it is suitable for many thin liquid and lightly viscous, neutral, aggressive and non-flammable liquids (max. 600 mPas). Its sophisticated, technically clear structure ensures an efficient and safe use when transferring a wide range of media.
- The drum pump motor is characterized not only by its lightweight (5,5 kg) but also by its elegant design and ease of use. The non-stationarily and stationarily usable drive is particularly suitable for intermittent operation. As externally ventilated motor it has an optimal air cooling, low noise and ensures high operational safety and long lifetime.
- The coated motor housing made of Aluminium ensures a high chemical resistance in case of aggressive vapours of acids and alkalies.
- The standard integrated low voltage release is intended to prevent an uncontrolled start of the drum pump motor after a power failure or voltage drop and thus guarantees maximum safety.
- The flow rate of the media to be pumped can be regulated by a speed control that is integrated in a keyboard at the top of the motor handle. By means of four speed steps flow rates of 50, 60, 80 and 100 percent can be selected. Therefore the flow rate can be adjusted to the needs of the user.
- The maximum density of the media is for the JP-360 universal motor 1,5, the maximum viscosity 600 mPas.



JP-360, 230 VAC, JP-PP(HC)41-1.000, test media water 20 °C, pressure pipe 1", oval gear meter, measured values: ± 5%

Electric universal motor JP-360

230 Volt, 50/60 Hz, 640 Watt, IP 55, with integrated low voltage release and integrated speed control. 5 m cable with plug.

Operating data JP-360

Flow rate (with hose and oval gear meter):	up to 93 l/min (Rotor)* up to 74 l/min (Impeller)*
Head:	up to 11 m (Rotor)* up to 26 m (Impeller)*
Viscosity:	up to 600 mPas*
Density:	up to 1,5*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values. Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

JP-360

Version	Voltage	Order No.
without LVR, with SC	230 V 1~, 50/60 Hz, 640 W	1360 2302
with LVR + SC	230 V 1~, 50/60 Hz, 640 W	1360 2303

LVR: Low voltage release
SC: Speed control

Integrated electronic speed control

The speed of the drum pump motor JP-360 can be controlled electronically via an integrated display on the handle. This enables an easy adjustment of the flow rate by the user.

BARRELPUMP.IR

JP-380 Electric universal motor


230 Volt, 50/60 Hz, 825 Watt, IP 55



Description

- The drive JP-380 is a compactly built, not explosion-proof, externally ventilated universal motor.
- This handy, very robust and powerful motor can be used to drive the suction tubes of drum pumps. In this combination it is suitable for many thin liquid and lightly viscous, neutral, aggressive and non-flammable liquids (max. 1.000 mPas). Its sophisticated, technically clear structure ensures an efficient and safe use when transferring a wide range of media.
- The drum pump motor is characterized not only by its lightweight (6 kg) but also by its elegant design and ease of use. The non-stationarily and stationarily usable drive is particularly suitable for intermittent operation. As externally ventilated motor it has an optimal air cooling, low noise and ensures high operational safety and long lifetime.

- The coated motor housing made of Aluminium ensures a high chemical resistance in case of aggressive vapours of acids and alkalis.
- The standard integrated low voltage release is intended to prevent an uncontrolled start of the drum pump motor after a power failure or voltage drop and thus guarantees maximum safety.
- The flow rate of the media to be pumped can be regulated by a speed control that is integrated in a keyboard at the top of the motor handle. By means of four speed steps flow rates of 50, 60, 80 and 100 percent can be selected. Therefore the flow rate can be adjusted to the needs of the user.
- The maximum density of the media is for the JP-380 universal motor 1,9, the maximum viscosity 1.000 mPas.



JP-380, 230 VAC, JP-PP(HC)41-1.000, test media water 20 °C, pressure pipe 1", oval gear meter, measured values: ± 5%

Electric universal motor JP-380

230 Volt, 50/60 Hz, 825 Watt, IP 55, with integrated low voltage release and integrated speed control. 5 m cable with plug.

Operating data JP-380

Flow rate (with hose and oval gear meter):	up to 112 l/min (Rotor)* up to 83 l/min (Impeller)*
Head:	up to 16 m (Rotor)* up to 37 m (Impeller)*
Viscosity:	up to 1.000 mPas*
Density:	up to 1,9*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values. Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

JP-380

Version	Voltage	Order No.
without LVR, with SC	230 V 1~, 50/60 Hz, 825 W	1380 2302
with LVR + SC	230 V 1~, 50/60 Hz, 825 W	1380 2303

LVR: Low voltage release
SC: Speed control

Integrated electronic speed control

The speed of the drum pump motor JP-380 can be controlled electronically via an integrated display on the handle.

This enables an easy adjustment of the flow rate by the user.

BARRELPUMP.IR

JP-400 Explosion-proof electric universal motor


230 Volt, 50/60 Hz, 550 Watt, IP 54, Ex de II A T6

Description

- The drive JP-400 is a compactly built, robust explosion-proof universal motor that is built and approved in accordance with the latest explosion protection guidelines (ATEX 2014/34/EC). The collector motor is explosion-proof according to II 2G Ex de IIA T6 and has an EC-type examination certificate ZELM 09 ATEX 0425 X. The electric motor Ex-JP-400 offers in addition to the air operated motors maximum protection when pumping flammable media or for use in hazardous environments. At such applications separate authorizations for the drive motor and the pump tube acc. directives ATEX 2014/34/EC are required.
- The handy and powerful device can be used as a drive for the ATEX certified sealless pump tubes made of Stainless steel (Ø 41 mm), the mixing pump tubes in Stainless steel, the pump tubes in Stainless steel with mechanical seal or complete drum emptying function and the eccentric screw pump tubes series JP-700 SR

PTFE ATEX. In this combination the drive is suitable for many thin liquid to viscous, neutral, lightly aggressive and easily flammable media with a flash point below 55 °C. Its sophisticated, technically clear structure ensures an efficient and safe use when transferring the wide range of media.

- The drum pump motor is characterized in addition to its robustness by its elegant design and ease of use. The non-stationarily and stationarily usable drive is particularly suitable for intermittently operation. As externally ventilated motor it has an optimal air cooling, low noise and ensures high operational safety and long lifetime.
- The standard in the on/off switch integrated low voltage release is intended to prevent an uncontrolled start of the drum pump motor after a power failure or voltage drop. Thus guarantees maximum safety.
- The maximum density of the media is for the JP-400 universal motor 1,5, the maximum viscosity 600 mPas.



JP-400, 230 VAC, JP-SS 41-1.000, test media water 20 °C, pressure pipe 1", oval gear meter, measured values: ± 5%

Electric universal motor JP-400

230 Volt, 50/60 Hz, 550 Watt, protection II 2G Ex de IIA T6, IP54, double insulated protection class II, with integrated low voltage release. 5 m cable without plug.

Operating data JP-400

Flow rate (with hose and oval gear meter): up to 97 l/min (Rotor)*
up to 71 l/min (Impeller)*

Head: up to 11 m (Rotor)*
up to 20 m (Impeller)*

Viscosity: up to 600 mPas*

Density: up to 1,5*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values. Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

JP-400

Version

Voltage

Order No.

without LVR

230 V 1~, 50/60 Hz, 550 W

1400 2300

with LVR

230 V 1~, 50/60 Hz, 550 W

1400 2301

LVR: Low voltage release

BARRELPUMP.IR



JP-440 Explosion-proof electric universal motor


230 Volt, 50/60 Hz, 400 Watt, IP 55, II 2G Ex db IIC T6 Gb

Description

- The drive JP-440 is a compactly built, robust explosion-proof universal motor that is built and approved in accordance with the latest explosion protection guidelines (ATEX 2014/34/EC) and IECEx. The collector motor is explosion-proof according to II 2G Ex db IIC T6 Gb and has an EC-type examination certificate BUREAU VERITAS 17 ATEX 1 088 X and IECEx EPS 17.0045 X. The electric motor Ex-JP-440 offers in addition to the air operated motors maximum protection when pumping flammable media or for use in hazardous environments. At such applications, separate authorizations for the drive motor and the pump tube acc. directives ATEX 2014/34/EC are required.
- The handy and powerful device (5,5 kg) can be used as a drive for the ATEX certified sealless pump tubes made of Stainless steel (Ø 41 mm), the mixing pump tubes of Stainless steel, the pump tubes of Stainless steel with mechanical seal or complete drum emptying function and the eccentric screw pump tubes series JP-700 SR PTFE ATEX. In this combination, the

drive is suitable for many thin liquid to viscous, neutral, lightly aggressive and easily flammable media with a flash point below 55 °C. Its sophisticated, technically clear structure ensures an efficient and safe use when transferring the wide range of media.

- The motor is characterized in addition to its robustness by its elegant design and ease of use. The non-stationarily and stationarily usable drive is particularly suitable for intermittent operation. As externally ventilated motor, it has an optimal air cooling, low noise and ensures high operational safety and long lifetime.
- The standard in the on/off switch integrated low voltage release is intended to prevent an uncontrolled start of the drum pump motor after a power failure or voltage drop. Thus guarantees maximum safety.
- The maximum density of the media is for the JP-440 universal motor 1,3, the maximum viscosity 400 mPas.



JP-440, 230 VAC, JP-SS 41-1000, test media water 20 °C, pressure pipe 1", oval gear meter, measured values: ± 5%

Electric universal motor JP-440

230 Volt, 50/60 Hz, 400 Watt, protection class II 2G Ex db IIC T6 Gb, IP 55, with integrated low voltage release. 5 m cable without plug. Optional with Ex-plug.

Operating data JP-440

Flow rate (with hose and oval gear meter):	up to 82 l/min (Rotor)*
	up to 61 l/min (Impeller)*
Head:	up to 9 m (Rotor)*
	up to 20 m (Impeller)*
Viscosity:	up to 400 mPas*
Density:	up to 1,3*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values. Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

JP-440	Version	Voltage	Order No.
	without LVR	230 V 1 ~, 50/60 Hz, 400 W	1440 2300
		115 V 1 ~, 60 Hz, 400 W	1440 1150
	with LVR	230 V 1 ~, 50/60 Hz, 400 W	1440 2301
		115 V 1 ~, 60 Hz, 400 W	1440 1151

LVR: Low voltage release

JP-460 Explosion-proof electric universal motor


230 Volt, 50/60 Hz, 640 Watt, IP 55, II 2G Ex db IIC T6 Gb

Description

- The drive JP-460 is a compactly built, robust explosion-proof universal motor that is built and approved in accordance with the latest explosion protection guidelines (ATEX 2014/34/EC) and IECEx. The collector motor is explosion-proof according to II 2G Ex db IIC T6 Gb and has an EC-type examination certificate BUREAU VERITAS 17 ATEX 1 088 X and IECEx EPS 17.0045 X. The electric motor Ex-JP-460 offers in addition to the air operated motors maximum protection when pumping flammable media or for use in hazardous environments. At such applications, separate authorizations for the drive motor and the pump tube acc. directives ATEX 2014/34/EC are required.
- The handy and powerful device (6 kg) can be used as a drive for the ATEX certified sealless pump tubes made of Stainless steel (Ø 41 mm), the mixing pump tubes of Stainless steel, the pump tubes of Stainless steel with mechanical seal or complete drum emptying function and the eccentric screw pump tubes series JP-700 SR

PTFE ATEX. In this combination, the drive is suitable for many thin liquid to viscous, neutral, lightly aggressive and easily flammable media with a flash point below 55 °C. Its sophisticated, technically clear structure ensures an efficient and safe use when transferring the wide range of media.

- The motor is characterized in addition to its robustness by its elegant design and ease of use. The non-stationarily and stationarily usable drive is particularly suitable for intermittent operation. As externally ventilated motor it has an optimal air cooling, low noise and ensures high operational safety and long lifetime.
- The standard in the on/off switch integrated low voltage release is intended to prevent an uncontrolled start of the drum pump motor after a power failure or voltage drop. Thus guarantees maximum safety.
- The maximum density of the media is for the JP-460 universal motor 1,5, the maximum viscosity 600 mPas.



JP-460, 230 VAC, JP-SS 41-1000, test media water 20 °C, pressure pipe 1", oval gear meter, measured values: ± 5%

Electric universal motor JP-460

230 Volt, 50/60 Hz, 640 Watt, protection class II 2G Ex db IIC T6 Gb, IP 55, with integrated low voltage release, 5 m cable without plug.

Optional with Ex-plug.

Operating data JP-460

Flow rate (with hose and oval gear meter):	up to 93 l/min (Rotor)*
	up to 74 l/min (Impeller)*
Head:	up to 11 m (Rotor)*
	up to 26 m (Impeller)*
Viscosity:	up to 600 mPas*
Density:	up to 1,5*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values. Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%



JP-460	Version	Voltage	Order No.
	without LVR	230 V 1~, 50/60 Hz, 640 W	1460 2300
		115 V 1~, 60 Hz, 640 W	1460 1150
	with LVR	230 V 1~, 50/60 Hz, 640 W	1460 2301
		115 V 1~, 60 Hz, 640 W	1460 1151

LVR: Low voltage release

JP-480 Explosion-proof electric universal motor

230 Volt, 50/60 Hz, 825 Watt, IP 55, II 2G Ex db IIC T6 Gb




Description

- The drive JP-480 is a compactly built, robust explosion-proof universal motor that is built and approved in accordance with the latest explosion protection guidelines (ATEX 2014/34/EC) and IECEx. The collector motor is explosion-proof according to II 2G Ex db IIC T6 Gb and has an EC-type examination certificate BUREAU VERITAS 17 ATEX 1 088 X and IECEx EPS 17.0045 X. The electric motor Ex-JP-480 offers in addition to the air operated motors maximum protection when pumping flammable media or for use in hazardous environments. At such applications separate authorizations for the drive motor and the pump tube acc. directives ATEX 2014/34/EC are required.
- The handy and powerful device (6,5 kg) can be used as a drive for the ATEX certified sealless pump tubes made of Stainless steel (Ø 41 mm), the mixing pump tubes of Stainless steel, the pump tubes of Stainless steel with mechanical seal or complete drum emptying function and the eccentric screw pump tubes series JP-700 SR PTFE ATEX. In this combination the

drive is suitable for many thin liquid to viscous, neutral, lightly aggressive and easily flammable media with a flash point below 55 °C. Its sophisticated, technically clear structure ensures an efficient and safe use when transferring the wide range of media.

- The motor is characterized in addition to its robustness by its elegant design and ease of use. The non-stationarily and stationarily usable drive is particularly suitable for intermittent operation. As externally ventilated motor, it has an optimal air cooling, low noise and ensures high operational safety and long lifetime.
- The standard in the on/off switch integrated low voltage release is intended to prevent an uncontrolled start of the drum pump motor after a power failure or voltage drop. Thus guarantees maximum safety.
- The maximum density of the media is for the JP-480 universal motor 1,9, the maximum viscosity 1000 mPas.



JP-480, 230 VAC, JP-SS 41-1000, test media water 20 °C, pressure pipe 1", oval gear meter, measured values: ± 5%

Electric universal motor JP-480

230 Volt, 50/60 Hz, 825 Watt, protection class II 2G Ex db IIC T6 Gb, IP 55, with integrated low voltage release, 5 m cable without plug.

Optional with Ex-plug.

Operating data JP-480

Flow rate (with hose and oval gear meter): up to 112 l/min (Rotor)*
up to 83 l/min (Impeller)*

Head: up to 16 m (Rotor)*
up to 37 m (Impeller)*

Viscosity: up to 1.000 mPas*

Density: up to 1,9*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values. Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%



JP-480	Version	Voltage	Order No.
without LVR		230 V 1~, 50/60 Hz, 825 W	1480 2300
		115 V 1~, 60 Hz, 825 W	1480 1150
with LVR		230 V 1~, 50/60 Hz, 825 W	1480 2301
		115 V 1~, 60 Hz, 825 W	1480 1151

LVR: Low voltage release

JP-AIR1 Explosion-proof air operated motor

300 Watt at max. 6 bar operating pressure, Ex 2GD c IIC T6 (80 °C) X



made of Aluminium

Description

- JP-AIR 1 is a compactly built, robust explosion-proof air operated motor in accordance with the latest explosion protection guidelines ATEX 2014/34/EC, category 2. It is explosion-protected according to Ex 2 GD c IIC T6 (80 °C) X and has a type-certificate IBEX U05 ATEX B007 X. JP-AIR 1 provides beside other air operated motors and the electric motors JP-400, JP-440, JP-460, JP-480 maximum safety when pumping flammable media or for use in hazardous environments. At such applications, for the drive motor and the pump tube, separate approvals acc. to directive ATEX 2014/34/EC are required and a potential equalization has to be installed.
- This handy and powerful device (2,1 kg) can be used as a drive for the laboratory pump tubes (not Ex-certified) or in hazardous areas for the ATEX certified sealless pump tubes made of Stainless steel (Ø 41 mm), the mixing pump tubes in Stainless steel, the Stainless steel pump tubes with mechanical seal or complete drum emptying function. In combination with ATEX certified pump tubes, the drive is suitable for many low-viscous, neutral, lightly aggressive media and especially for highly flammable media

with a flash point below 55 °C. Its sophisticated, technically clear structure ensures an efficient and safe use when transferring the wide range of media.

- This drum pump motor is characterized in addition to its robustness by its elegant design and ease of use. The non-stationarily and stationarily usable drive is particularly suitable for intermittent operation. The construction of the motor guarantees a high operational safety and a long lifetime.
- The very robust Aluminium motor housing ensures a good chemical resistance in case of aggressive solvent vapours.
- This air operated motor is supplied with a silencer and a ball valve at the air inlet for controlling the compressed air and thereby the motor speed.
- The maximum density of the media is for the explosion-proof air operated motor JP-AIR 1 1,3, the maximum viscosity 400 mPas.



JP-AIR1, JP-SS 41-1.000 test media water 20 °C, pressure pipe 1", oval gear meter, measured values: ± 5%

Air operated motor JP-AIR 1

300 Watt at max. 6 bar operating pressure, with silencer and a Brass ball valve for control compressed air. This regulates speed of the motor and varies pumping capacity.

Operating data JP-AIR 1

Flow rate (with hose and oval gear meter):	up to 78 l/min (Rotor)* up to 60 l/min (Impeller)*
Head:	up to 9 m (Rotor)* up to 13 m (Impeller)*
Viscosity:	up to 400 mPas*
Density:	up to 1,3*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values.
Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

BARRELPUMP.IR



JP-AIR 1

Performance

Order No.

300 W

3001 0300

300 Watt at max. 6 bar
operating pressure

Air consumption under load 13 l/sec.

JP-AIR2 Explosion-proof air operated motor

600 Watt at max. 6 bar operating pressure, Ex 2GD c IIC T6 (80 °C) X


made of Aluminium

Description

- JP-AIR 2 is a compactly built, robust explosion-proof air operated motor in accordance with the latest explosion protection guidelines ATEX 2014/34/EC, category 2. It is explosion-protected according Ex 2 GD c IIC T6 (80 °C) X and has a type-certificate IBEX U05 ATEX B007 X. JP-AIR 2 provides beside other air operated motors and the electric motors JP-400, JP-440, JP-460, JP-480 maximum safety when pumping flammable media or for use in hazardous environments. At such applications for the drive motor and the pump tube separate approvals acc. to directive ATEX 2014/34/EC are required and a potential equalization has to be installed.
- This handy and powerful device (1,5 kg) can be used as a drive for the laboratory pump tubes (not Ex-certified) or in hazardous areas for the ATEX certified sealless pump tubes made of Stainless steel (Ø 41 mm), the mixing pump tubes in Stainless steel, the Stainless steel pump tubes with mechanical seal or residual emptying function and the eccentric screw pump tubes of series JP-700 SR PTFE ATEX. In combination with ATEX certified pump tubes, the drive is suitable for many low-viscous, neutral, lightly aggressive media and for highly flam-

mable media with a flash point below 55 °C. Its sophisticated, technically clear structure ensures an efficient and safe use when transferring a wide range of media.

- The motor is characterized in addition to its robustness by its elegant design and ease of use. The non-stationarily and stationarily usable drive is particularly suitable for intermittent operation. The construction of the motor guarantees a high operational safety and a long lifetime.
- The very robust Aluminium motor housing ensures a good chemical resistance in case of aggressive solvent vapours.
- The air operated motor is supplied with a silencer. On the handle is an on/off starting button that can be fixed.
- The maximum density of the media is for the explosion-proof air operated motor JP-AIR 2 1,5, the maximum viscosity 600 mPas.



JP-AIR2, JP-SS 41-1.000, test media water 20 °C, pressure pipe 1", oval gear meter, measured values: ± 5%

Air operated motor JP-AIR 2

600 Watt at max. 6 bar working pressure, with silencer and on/off switch.

Operating data JP-AIR 2

Flow rate (with hose and oval gear meter):	up to 80 l/min (Rotor)* up to 66 l/min (Impeller)*
Head:	up to 10 m (Rotor)* up to 15 m (Impeller)*
Viscosity:	up to 600 mPas*
Density:	up to 1,5*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values. Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

BARRELPUMP.IR



Performance	Order No.
600 W	3002 0600

600 Watt at max. 6 bar operating pressure
Air consumption under load 15 l/sec.

JP-AIR3 Explosion-proof air operated motor

400 Watt at max. 6 bar operating pressure, Ex 2GD c IIC T6 (80 °C) X


made of Stainless steel

Description

- JP-AIR 3 is a compactly built, robust explosion-proof air operated motor in accordance with the latest explosion protection guidelines ATEX 2014/34/EC, category 2. The pneumatic motor is explosion-protected to Ex 2 GD c IIC T6 (80 °C) X and has a type-certificate IBEX U05 ATEX B007 X. JP-AIR 3 provides among other air operated motors and the electric motors JP-400, JP-440, JP-460, JP-480 maximum safety when pumping flammable media or for use in hazardous environments. At such applications, for the drive motor and the pump tube separate approvals acc. to directive ATEX 2014/34/EC are required and a potential equalization has to be installed.
- This handy and powerful device (1,9 kg) can be used as a drive for the laboratory pump tubes (not ex-certified) or in hazardous areas for the ATEX certified stainless pump tubes made of Stainless steel (Ø 41 mm), the mixing pump tubes in Stainless steel, the Stainless steel pump tubes with mechanical seal or residual emptying function and the eccentric screw pump tubes of series JP-700 SR PTFE ATEX. In combination with ATEX certified pump tubes the drive is suitable for many low-viscous, neutral, lightly aggressive media and

for highly flammable media with a flash point below 55 °C. Its sophisticated, technically clear structure ensures an efficient and safe use when transferring the wide range of media.

- The motor is characterized in addition to its robustness by its elegant design and ease of use. The non-stationarily and stationarily usable drive is particularly suitable for intermittent operation. The construction of the motor guarantees a high operational safety and a long lifetime.
- The very robust Stainless steel 316Ti motor housing ensures a good chemical resistance when aggressive solvent vapours are present.
- The air operated motor is supplied with two silencers and a ball valve at the air inlet for controlling the compressed air and thereby the motor speed.
- The maximum density of the media is for the explosion-proof air operated motor JP-AIR 3 at 1,5, the maximum viscosity 600 mPas.



JP-AIR3, JP-SS 41-1.000, test media water 20 °C, pressure pipe 1", oval gear meter, measured values: ± 5%

Air operated motor JP-AIR 3

400 Watt at max. 6 bar operating pressure, with silencer and a Brass ball valve for control the compressed air. This regulates speed of the motor and varies pumping capacities.

Operating data JP-AIR 3

Flow rate (with hose and oval gear meter): up to 91 l/min (Rotor)*
up to 71 l/min (Impeller)*

Head: up to 13 m (Rotor)*
up to 25 m (Impeller)*

Viscosity: up to 600 mPas*

Density: up to 1,5*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values.
Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

All motors can be combined outside hazardous areas with all pump tubes over the hand wheel. Suitable pump tubes can be found on pages 40 to 45.



JP-AIR 3

Performance

Order No.

400 W

3003 0400

400 Watt at max. 6 bar
operating pressure

Air consumption under load 12 l/sec.

Pump tubes made of Polypropylene

for pumping aggressive media such as acids, alkalis and detergents, Ø 41 mm

Rotor/Impeller



Axial (Rotor)

Standard in all pump tubes.

- Pump tubes with rotor are used when high capacities and low heads are required.
- A typical application is the decanting of drums and containers at same level.
- **A rotor made of Stainless steel 316Ti is available as an option for Stainless steel pump tubes.**

Standard tube lengths (available from stock)

700 mm • 1.000 mm • 1.200 mm • 1.500 mm • 1.800 mm

Special lengths (available within 1-2 days)

from 200 mm up to 3.000 mm
(Depending on the pump tube material and the medium temperature)



Polypropylene = PP pump tubes up to 50 °C

- For aggressive and hardly flammable media.
- Especially suitable for aggressive media such as cleaning agents, acids and alkalis.
- Drive shaft made of Stainless steel 316Ti or Hastelloy 2.4610.
- Hose connection 1" included (¾" or 1¼" also possible).
- Maximum medium temperature 50 °C.



Radial (Impeller)

- If larger heads at lower flow rates are required, pump tubes with radial impellers are the right choice.
- For this, a special pump foot is required. In any case, it is to be considered that the actual performance of a pump tube depends on the power of the used motor.
- **An impeller made of Stainless steel 316Ti is available as an option for Stainless steel pump tubes.**

Material of pump tube	Pump tube diameter	Pump tube length	Version	Order No.
Polypropylene (SS) Stainless steel drive shaft 316Ti	Ø 41 mm	700 mm	Rotor	2641 0070
			Impeller	2641 0071
	Ø 41 mm	1.000 mm	Rotor	2641 0100
			Impeller	2641 0101
	Ø 41 mm	1.200 mm	Rotor	2641 0120
			Impeller	2641 0121
	Ø 41 mm	1.500 mm	Rotor	2641 0150
			Impeller	2641 0151
	Ø 41 mm	1.800 mm	Rotor	2641 0180
			Impeller	2641 0181

Polypropylene (HC) Hastelloy drive shaft 2.4610	Ø 41 mm	700 mm	Rotor	2141 0070
			Impeller	2141 0071
	Ø 41 mm	1.000 mm	Rotor	2141 0100
			Impeller	2141 0101
	Ø 41 mm	1.200 mm	Rotor	2141 0120
			Impeller	2141 0121
	Ø 41 mm	1.500 mm	Rotor	2141 0150
			Impeller	2141 0151
	Ø 41 mm	1.800 mm	Rotor	2141 0180
			Impeller	2141 0181

Examples of media

Formic acid (50%)
Ammonia
Boric acid
Distilled water
Fertilizer solutions
Iron II and III-chloride
Acetic acid (80%)
Photo developer
Fruit acids
Potassium hydroxide solution
Copper chloride
Lactic acid
Sodium hydroxide solution
Phosphoric acid
Hydrochloric acid
Sulfuric acid up to (90%)
Hydrogen peroxide
Citric acid
and many other media

- Special lengths from 200 to 3.000 mm are available on request with short delivery times.

BARRELPUMP.IR

Pump tubes made of PVDF for pumping aggressive media such as highly concentrated acids and alkalies, Ø 41 mm



Polyvinylidene fluoride = PVDF pump tubes up to 90 °C

- For aggressive and hardly flammable media.
- Especially suitable for aggressive media such as high concentrated acids and alkalies.
- Drive shaft made of Hastelloy 2.4610.
- Hose connection 1" included (¾" or 1¼" also possible).
- Maximum medium temperature 90 °C.

Examples of media

Hydrobromic acid
 Chloric acid
 Chromic acid
 Hydrofluoric acid
 Sodium hypochlorite
 Nitric acid and
 Sulfuric acid > 90 °C

All media, mentioned at the Polypropylene pump tubes can be pumped also.

Material of pump tube	Pump tube diameter	Pump tube length	Version	Order No.
Polyvinylidene-fluoride (PVDF) Hastelloy drive shaft 2.4610	Ø 41 mm	700 mm	Rotor	2341 0070
			Impeller	2341 0071
	Ø 41 mm	1.000 mm	Rotor	2341 0100
			Impeller	2341 0101
	Ø 41 mm	1.200 mm	Rotor	2341 0120
			Impeller	2341 0121
	Ø 41 mm	1.500 mm	Rotor	2341 0150
			Impeller	2341 0151

- Special lengths are available on request with short delivery times.

Pump tubes made of Aluminium

for transferring mineral oil products up to 1.000 mPas, Ø 41 mm



Aluminium = ALU pump tubes up to 90 °C

- For neutral and hardly flammable media.
- Especially suitable for mineral oil products up to 1.000 mPas.
- Drive shaft made of Stainless steel 316Ti.
- Hose connection 1" included (¾" or 1¼" also possible).
- Maximum medium temperature 90 °C.

Examples of media

Drilling emulsions
 Diesel
 Liquid soap
 Liquid wax
 Transmission oils
 Fuel oil
 Hydraulic oils
 Machine oils
 Mineral oils
 and motor oils

Material of pump tube	Pump tube diameter	Pump tube length	Version	Order No.
Aluminium (ALU) Stainless steel drive shaft 316Ti	Ø 41 mm	700 mm	Rotor	2441 0070
			Impeller	2441 0071
	Ø 41 mm	1.000 mm	Rotor	2441 0100
			Impeller	2441 0101
	Ø 41 mm	1.200 mm	Rotor	2441 0120
			Impeller	2441 0121
	Ø 41 mm	1.500 mm	Rotor	2441 0150
			Impeller	2441 0151

- Special lengths up to 3.000 mm are available on request with short delivery times.

BARRELPUMP.IR

Pump tubes made of Stainless steel 316Ti

for transferring neutral, lightly aggressive media and especially flammable media like solvents and for use in food industry, Ø 41 mm



Stainless steel = SS pump tubes with Ex approval, outside Ex-areas max. 90 and 120 °C

- With Stainless steel pump tubes all neutral, low viscous media such as organic and inorganic diluted acids and alkalis are mainly pumped. In addition these ATEX compliant pump tubes are used specifically for pumping highly combustible media such as solvents or gasoline and for use in explosive environments.
- Suitable for flammable media up to temperature class 4 and use in Ex-zone 0.
- The pump tubes in Stainless steel with a carbon bearing approved for the food sector are used since many years in the food industry and the beverage industry.

- Drive shaft made of Stainless steel 316Ti.
- Hose connection 1" included (¾" or 1¼" also possible).
- EC type examination certificate number ZELM 09 ATEX 0424X.
- Maximum medium temperature 90 °C (with PTFE rotor) or 120 °C (with SS rotor) outside Ex areas.

Examples of media

Acetone
Alcohol
Ammonia
Gasoline
Flammable solvents
Potassium hydroxide solution
Sodium hydroxide solution
Nitrovarnishes
Perchloroethylene
Phosphoric acid
Sulfuric acid (up to 7.5% and over 90%)
Trichloroethylene
Toluene

In addition, the Stainless steel pump tubes are suitable for transferring thin fluid food such as fruit juices, milk, edible oils and all other listed under Aluminium pump tubes media.

Material of pump tube	Pump tube diameter	Pump tube length	Version	Order No.
Stainless Steel 316Ti Stainless steel shaft EC type-certificate ZELM 09 ATEX 0424 X Ex II1/2 G c II B T4	Ø 41 mm	700 mm	Rotor	2241 0070
			Impeller	2241 0071
	Ø 41 mm	1.000 mm	Rotor	2241 0100
			Impeller	2241 0101
	Ø 41 mm	1.200 mm	Rotor	2241 0120
			Impeller	2241 0121
	Ø 41 mm	1.500 mm	Rotor	2241 0150
			Impeller	2241 0151
	Ø 41 mm	1.800 mm	Rotor	2241 0180
			Impeller	2241 0181
	Ø 41 mm	2.100 mm	Rotor	2241 0210
			Impeller	2241 0211
	Ø 41 mm	2.400 mm	Rotor	2241 0240
			Impeller	2241 0241
	Ø 41 mm	2.700 mm	Rotor	2241 0270
			Impeller	2241 0271
	Ø 41 mm	3.000 mm	Rotor	2241 0300
			Impeller	2241 0301
Rotor or impeller made of Stainless steel full material for Stainless steel pump tubes Ø 41 mm			Rotor	2710
			Impeller	2725

BARRELPUMP.IR

Mixing pump tubes made of Polypropylene or Stainless steel for mixing or emptying drums and IBCs

Mixing pump tubes are suitable for those applications where low viscous to lightly viscous media are to be mixed in drums and other containers and after that pumped out.

The mixing pump tubes made of Polypropylene with a shaft of Hastelloy are used especially for aggressive media like acids and alkalis. Mixing pump tubes made of Stainless steel are used primarily for

neutral, lightly aggressive and flammable media. The pump tubes are approved for use in Ex-zone 0. They fulfill all national and international standards for pumping flammable media and here especially the ATEX directives.



Mixing pump tube made of Polypropylene (Mix PP), seamless construction with double function mixing and pumping.

- Suction tube length 1.000/1.200 mm, suction tube diameter 50/41 mm.
- Drive shaft in Hastelloy 2.4610.
- Hose connection 1" included (¾" or 1¼" also possible).
- The suction tube length of 1.000 mm is suitable for mixing and transferring media out of 200-liter drums.

- The suction tube length of 1.200 mm is the right choice for circulating media in containers and to empty the containers.
- The motors JP-180, JP-280, JP-360 and JP-380 and the air operated motors have proven themselves as drives for the mixing pump tubes.

Material of pump tube	Pump tube diameter	Pump tube length	Order No.
Polypropylene (PP)	Ø 50/41 mm	1.000 mm	2141 0102
Drive shaft Hastelloy 2.4610	Ø 50/41 mm	1.200 mm	2141 0122



Mixing pump tube made of Stainless steel 316Ti (Mix SS) seamless construction with the double function mixing and pumping.

Approved for pumping flammable liquids as paints and varnishes!

- Suction tube length 1.000/1.200 mm, suction tube diameter 50/41 mm.
- Drive shaft in Stainless steel 316Ti.

- Hose connection 1" included (¾" or 1¼" also possible).
- The suction tube length of 1.000 mm is suitable for mixing and transferring media out of 200-liter drums.
- The suction tube length of 1.200 mm is the right choice for circulating media in containers and to empty the containers.
- The motors JP-180, JP-280, JP-360 and JP-380 as well as in hazardous areas the electric motors JP-400, JP-440, JP-460, JP-480 and the air operated motors have proven themselves as drives for the mixing pump tubes.
- EC type examination certificate number ZELM 09 ATEX 0424X.

Material of pump tube	Pump tube diameter	Pump tube length	Order No.
Stainless steel 316Ti	Ø 50/41 mm	1.000 mm	2241 0102
Drive shaft Stainless steel	Ø 50/41 mm	1.200 mm	2241 0122

BARRELPUMP.IR

Pump tube made of Stainless steel with mechanical seal for pumping sticky or crystallizing media

Normally sealless pump tubes can be used for almost all applications. Only with sticky, crystallizing, heavily polluted media or when the container is pre-pressurized, pump tubes with mechanical seal are necessarily preferable.

These tubes are not allowed to run dry.

EC type examination certificate number ZELM 09 ATEX 0424X Ex II 1/2 G c IIB T4.

Stainless steel 316Ti = SS pump tubes with mechanical seal

- Suitable for pumping thin fluid to middle viscous media, whether neutral, lightly aggressive or flammable.
- The use of a mechanical seal is mandatory when pumping sticky or crystallizing and heavily soiled or solid containing media that prevent the use of a sealless pump tube with carbon bearing.
- The mechanical seal used in the pump housing prevents that the pumped medium can flow in the inner tube.
- After pumping the sticky or crystallizing media the pump must be absolutely flushed and cleaned (medium temperature up to 90 °C with PTFE-rotor).

- In contrast to the sealless pump tubes that can be used in 95% of all applications and where dry running because of the construction is not a problem, drum pumps with mechanical seal are not allowed to run dry.



Examples of media

For special applications with sticky, crystallizing, dirty or solids-containing fluids at which no medium is allowed to flow into inner tube.

Attention: the pump tubes with mechanical seal are not allowed to run dry.

- Special lengths up to 3.000 mm are available on request with short delivery times.

Material of pump tube	Pump tube diameter	Pump tube length	Order No.
Stainless steel 316Ti Drive shaft Stainless steel	Ø 41 mm	700 mm	2741 0070
	Ø 41 mm	1.000 mm	2741 0100
	Ø 41 mm	1.200 mm	2741 0120
	Ø 41 mm	1.500 mm	2741 0150
	Ø 41 mm	1.800 mm	2741 0180
	Ø 41 mm	2.100 mm	2741 0210
	Ø 41 mm	2.400 mm	2741 0240
	Ø 41 mm	2.700 mm	2741 0270
	Ø 41 mm	3.000 mm	2741 0300

Pump tubes made of Stainless steel for complete emptying of drums or containers

With a residual emptying pump tube in Stainless steel, neutral, lightly aggressive, dangerous and economically valuable liquids can be transferred nearly completely out of drums and containers.

By a handle below the hand wheel, the pump foot can be closed. This prevents the medium from flowing out of the hose and the suction tube back into the drum after motor has been switched off.

EC type examination certificate number ZELM 09 ATEX 0424X
Ex II 1/2 G c IIB T4.

Due to the fact that with a remaining quantity of 0,1 l only minimal residues remain inside the drums and containers, the medium can be used optimally. Especially no additional costs or time incur required for emptying the containers in another way.

Pump tube in Stainless steel 1.4571 with complete drum emptying function and mechanical seal

- The motors JP-180, JP-280, JP-460 and JP-480 and the air operated motors are all compatible with the complete drum emptying pump tubes.
- The pump tube length 1.000 mm is used when emptying 200 liter drums.
- The pump tube length 1.200 mm is used when emptying containers.
- In contrast to the sealless pump tubes that can be used in 95% of all applications and that can run dry cause of its construction, drum pumps with mechanical seal are not allowed to run dry.



Applications

Optimal container emptying and product use.

Remaining quantity of 0,1 liters per barrel.

No leakage when moving the pump to another drum.









No additional costs incur when emptying the drums in another way.

Attention:

The pump tubes with mechanical seal are not allowed to run dry.

Material of pump tube	Pump tube diameter	Pump tube length	Order No.
Stainless steel 316Ti	Ø 41 mm	1.000 mm	2841 0100
Drive shaft Stainless steel	Ø 41 mm	1.200 mm	2841 0120

Accessories for drum and container pumps

		Order No.
	<p>Barrel adapter made of Polypropylene (PP and PVDF pump tube) for fixing the barrel pump in the bung hole of a drum, diameter of pump tube 41 mm, G 2".</p>	Ø 41 9001
	<p>Barrel adapter made of Stainless steel for secure fixing of drum pump in bung hole of a drum, diameter of pump tube 41 mm, G 2".</p> <p>The barrel adapters fit due to their 2" thread in 60 and 200 liter steel drums. For use with plastic drums or plastic containers, they can be combined with the thread adapters on page 10.</p>	Ø 41 9002
	<p>Bounding ground set Set consisting of 4 cables with connection clamps. These ground wires with connection clamps are absolute necessary when pumping flammables or for use in hazardous areas. This set can be used as an electric conductive connection between the drum pump and the container for earthing and balancing out the energy resources.</p>	9003 0,5 m 9003/1 1 m 9003/2 2 m 9003/3 3 m 9003/4
	<p>Safety clamp made of tool steel for secure fixing of barrel pump in open containers and open drums.</p>	9005
	<p>Stainless steel hose clamp 1/2" or 3/4" or 1" or 1 1/4" for secure fixing of hose at hose barb Please specify when ordering the nominal width.</p>	9004
	<p>Wall hanger for barrel pump Ø 41 mm for a secure storage of barrel pump if out of operation and for protection against damages.</p>	9006
	<p>Screw cap for IBC, IG 2" optional with barrel adapter PP Ø 41 mm IBC DN 225 (black) IBC DN 150 (red) IBC DN 225 (green) food IBC DN 150 (green) food Barrel adapter PP</p>	9071 9071a 9071b 9071c 9001
	<p>Strainer for protection the barrel pump when abrasive particles are present.</p> <p>Polypropylene Size of slots 1,5 x 12 mm, tube-Ø 40, 41 or 42 mm</p> <p>Stainless steel 316Ti Size of slots 1,5 x 20 mm, tube-Ø 41 mm</p> <p>PVDF Size of slots 1,5 x 12 mm, tube-Ø 41 mm</p>	9011 9012 9230
PP	Stainless steel 316Ti	

BARRELPUMP.IR

Accessories for drum and container pumps

Order No.



Nozzle made of Polypropylene

Housing and internal parts made of Polypropylene, valve seat and O-rings made of **FKM** or **EPDM** rotatable hose connection.

Flow rate: 80 l/min*
Viscosity: 800 mPas
Operating pressure: 3 bar*
Weight: 210 g

FKM	1/2"	9101
FKM	3/4"	9102
FKM	1"	9103
FKM	IG 1"	9120
EPDM	1/2"	9104
EPDM	3/4"	9105
EPDM	1"	9106
EPDM	IG 1"	9121



Nozzle made of PVDF

Housing and internal parts made of PVDF, valve seat and O-rings made of **FKM** or **EPDM** rotatable hose connection.

Flow rate: 80 l/min*
Viscosity: 800 mPas
Operating pressure: 3 bar*
Weight: 210 g

FKM	1/2"	9107
FKM	3/4"	9108
FKM	1"	9109
FKM	IG 1"	9122
EPDM	1/2"	9110
EPDM	3/4"	9111
EPDM	1"	9112
EPDM	IG 1"	9123
FFKM	1/2"	9113
FFKM	3/4"	9114
FFKM	1"	9115
FFKM	IG 1"	9116



Manual nozzle made of Polypropylene for AdBlue, with outlet spout in Ø 19 mm made of Stainless steel

Housing and internal parts made of white Polypropylene, valve seat and O-rings made of **FKM**, spring made of Stainless steel.

Flow rate: 40 l/min*
Operating pressure: max. 3,4 bar*

FKM	3/4"	9015
FKM	1"	9015b



Automatic nozzle made of Stainless steel for AdBlue, with a outlet spout in Ø 19 mm, swivel hose connection

Flow rate: 80 l/min*
Operating pressure: max. 3,4 bar*

	3/4"	9124
	1"	9125



Nozzle made of nickel-plated Brass, PTFE seals, rotatable hose connection

For filling and transferring neutral and aggressive media and liquids, also in the field of pharmaceutical and the food industry. Housing and internal parts are made of nickel-plated Brass. Seals made of PTFE.

Flow rate: 80 l/min*
Viscosity: 900 mPas
Operating pressure: 4 bar*
Medium temperature: max. 80 °C
Weight: 1 kg

Various connection options (Hose connection, thread)



	3/4"	9041
	1"	9042
	1 1/4"	9043
	AG 1"	9044
	AG 1 1/4"	9045
	IG 1"	9046

BARRELPUMP.IR

Alle physikalischen Angaben sind real gemessene Maximalwerte.
Prüfmedium: Wasser 20°C, 2 m horizontales Druckrohr 1", Ovalradzähler 1", Messwerte +/-5%.

IG: female thread AG: male thread

Accessories for drum and container pumps

		Order No.
	<p>Nozzle made of Stainless steel 316Ti for use in chemical, pharmaceutical and food-industry. Flow rate: 80 l/min* Viscosity: 900 mPas Operating pressure: 4 bar* Medium temperature: max. 80 °C Weight: 1 kg</p>	<p>1" AG 1" 9013 9013a</p>
	<p>Nozzle made of Aluminium for diesel, female thread, suitable to discharge hose male thread. Flow rate: 60 l/min* Hose connection ALU Hose connection ALU</p>	<p>9032</p> <p>3/4" 1" 9032a 9032b</p>
	<p>Emission proof drum adapter for pump tube diameter 41 mm, thread G 2". FKM-seals prevent emission of harmful gases and vapours out of the drum. A vacuum in drum is equalized by a valve. made of Polypropylene made of Brass made of Stainless steel 316Ti</p>	<p>9024 9025 9026</p>
	<p>PVC-hose crystal clear with fabric lining, suitable for non flammable, neutral and aggressive media. Operating pressure: 10 bar* Medium temperature: -35 °C up to +60 °C</p>	<p>3/4" 1" 1 1/4" 1 1/2" 9050 9051 9052 9053</p>
	<p>Universal chemical- and solvent hose, conductive inner wall homogeneous, smooth, EPDM (Ethylene Propylene-Rubber) conductive, suitable for many alkalies, acids, acetates, aldehydes, amines, esters, ethers and ketones, not suitable for carbonic gassy products and their derivatives as well as for oils and gasoline. Operating pressure: 16 bar* Temperature: -40 °C up to +90 °C</p>	<p>3/4" 1" 1 1/4" 1 1/2" 9055 9056 9057 9058</p>
<p>Multi purpose chemical hose, conductive inner wall homogeneous, smooth, PE-X (knitted Polyethylene), conductive, suitable for nearly all chemicals. Not suitable for oleum, brom and chlorosulfon acide. Operating pressure: 10 bar* Temperature: -25 °C bis +90 °C (also available in a food grade version)</p>	<p>3/4" 1" 1 1/4" 1 1/2" 9060 9061 9062 9063</p>	
<p>Mineral oil hose PN10 with fabric lining PN10 with fabric lining PN16 TW-hose PN16 TW-hose</p>	<p>3/4" 1" 1 1/4" 1 1/2" 9065 9066 9067 9068</p>	
<p>Rubber hose food grade BUTYL/BUTYL suitable for animal and vegetable fat and oils, milk products, mineral water, fruit juice and alcohol up to 92% Temperature: up to 120 °C</p>	<p>3/4" 1" 9069a 9069</p>	

AG: male thread

* All specified values are real measured maximum values.

* Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

BARRELPUMP.IR

Accessories for drum and container pumps

		Order No.
	<p>Hose connectors in Stainless steel with clamps made of Aluminium (connection to pump tube female thread 1 1/4", connection to nozzle female thread 1").</p>	9010
	<p>Clamping flange made of Polypropylene for IBC-Container (to fix a pump with Ø 40/41mm), Ø 140 mm, 4-holes, screw-hole circle 115 mm.</p>	9070
	<p>Discharge arc for transferring and filling liquids directly into other vessels. They are available in PP, ALU and Stainless steel 316Ti and can be connected directly at the discharge side of a drum pump via a wing nut.</p>	PP 9072 ALU 9073 SS 9074
	<p>Explosion proof plug - Explosion proof socket Ex de IIC T6, protection class IP 65, 16 Ampere. CEE round plug 3-pole 5-pole CEE socket 3-pole 5-pole</p>	5055 5056 5057 5058
	<p>Electronic flow meter to measure a big variety of media. Turbine gear meter are suitable for low viscous, water-like media and are available in PP, PVDF and Stainless steel. Oval gear meter measure the flow of viscous media and are also available in different materials. Volume setting or impulse output as an option.</p>	
		

Accessories of air operated motors



Service unit

For cleaning and lubrication of air. With manometer to adjust operating pressure (max. 10 bar).

Slot socket

Brass, G 3/8" male thread, for hose NW 9.

Air pressure hose

PVC-hose internally knitted NW 9, 3/8",
Max. operating pressure: 10 bar, temperature: -35 °C until +60 °C.



Ball valve

Brass chrom plated, to control air pressure and hereby speed of the air operated motors, both sides female thread R 3/8".

BARRELPUMP.IR

Drum pump sets

Further versions
on request

Drum pump sets for cleaning agents

Order No.

**Drum pump set JP-180 PP (HC) 1000**

Electric universal motor JP-180, 230 V, 50/60 Hz, 640 W internally ventilated motor, splash protection to IP 24, on/off switch, 5 m cable with plug, double isolated class II, over load protection switch with low voltage release.

Pump tube: Polypropylene, sealless, 1.000 mm, outer-Ø 41 mm, HC-shaft 2.4610, connection thread G 1 1/4", hose connection 1" (NW 25)

2 m PVC hose 1" (NW 25)

2 Hose clamps Stainless steel

1 Nozzle Polypropylene

Flow rate: up to 93 l/min (Rotor)*, up to 74 l/min (Impeller)*

Head: up to 11 m (Rotor)*, up to 26 m (Impeller)*

Medium temperature: up to 50 °C

Viscosity: up to 600 mPas*, **Density:** up to 1.5*

230 V
115 V1181 4110
1182 4110

Drum pump sets for highly concentrated acids and alkalis

Order No.

**Drum pump set JP-280 PVDF 1000**

Electric universal motor JP-280, 230 V, 50/60 Hz, 825 W internally ventilated motor, splash protection to IP 24, on/off switch, 5 m cable with plug, double isolated class II, over load protection switch with low voltage release.

Pump tube: PVDF, sealless, 1.000 mm, outer-Ø 41 mm, HC-shaft 2.4610, connection thread G 1 1/4", hose connection 1" (NW 25)

2 m Multi purpose chemical hose 1" (NW 25)

2 Hose clamps Stainless steel

1 Nozzle PVDF

Flow rate: up to 112 l/min (Rotor)*, up to 83 l/min (Impeller)*

Head: up to 16 m (Rotor)*, up to 37 m (Impeller)*

Medium temperature: up to 80 °C

Viscosity: up to 1.000 mPas*, **Density:** up to 1.9*

230 V
115 V1281 4112
1282 4112

Drum pump sets for mineral oil products up to 1.000 mPas

Order No.

**Drum pump set JP-280 ALU 1000**

Electric universal motor JP-280, 230 V, 50/60 Hz, 825 W internally ventilated motor, splash protection to IP 24, on/off switch, 5 m cable with plug, double isolated class II, over load protection switch with low voltage release

Pump tube: Aluminium, sealless, 1.000 mm, outer-Ø 41 mm, shaft Stainless steel, connection thread G 1 1/4", hose connection 1" (NW 25)

2 m Mineral oil hose 1" (NW 25)

2 Hose clamps Stainless steel

1 Nozzle Aluminium

Flow rate: up to 112 l/min (Rotor)*, up to 83 l/min (Impeller)*

Head: up to 16 m (Rotor)*, up to 37 m (Impeller)*

Medium temperature: up to 80 °C

Viscosity: up to 1.000 mPas*, **Density:** up to 1.9*

230 V
115 V1281 4111
1282 4111

* All specified values are real measured maximum values.

* Test medium water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

Attention: When using a nozzle, the flow rate is reduced to app. 60-80 l/min

(depends on the pump and application).

All drum pump sets with rotor

BARRELPUMP.IR

Drum pump sets

 Further versions
 on request

Drum pump sets for flammable such as petrol and solvents
Order No.

Drum pump set JP-400 SS 1000

Electric universal motor JP-400, 230 Volt, 50/60 Hz, 550 Watt, protection II 2G Ex de IIA T6, IP54, double insulated protection class II, with integrated low voltage release. 5 m cable **without plug**.

EC type examination certificate number **ZELM 09 ATEX 0425 X**

Pump tube: Stainless steel 316Ti, sealless, 1.000 mm, outer-Ø 41 mm, connection thread G 1¼",

EC type examination certificate number **ZELM 09 ATEX 0424 X**

2 m Multi purpose hose, conductive 1" (NW 25)

2 Hose connectors Stainless steel, clamps made of Aluminium, IG 1¼" or IG 1"

1 Nozzle Brass nickel plated

1 Bonding ground set

Flow rate: up to 97 l/min (Rotor)*, up to 71 l/min (Impeller)*

Head: up to 11 m (Rotor)*, up to 20 m (Impeller)*

Medium temperature: see Ex-certificate

Viscosity: up to 600 mPas*, **Density:** up to 1.5*

230 V

1402 4110


Drum pump set JP-440 SS 1000

Electric universal motor JP-440, 230 V, 50/60 Hz, 400 W, protection class II 2G Ex db IIC T6 Gb, IP 55, with integrated low voltage release, 5 m cable **without plug**. Optional with Ex-plug.

EC type examination certificate Bureau Veritas **EPS 17 ATEX 1 088 X**

IECEX Certificate of Conformity **IECEX EPS 17.0045 X**

Pump tube: Stainless steel 316Ti, sealless, 1.000 mm, outer-Ø 41 mm, connection thread G 1¼",

EC type examination certificate number **ZELM 09 ATEX 0424 X**

2 m Multi purpose hose, conductive 1" (NW 25)

2 Hose connectors Stainless steel IG 1¼" or IG 1"

1 Nozzle Brass nickel plated

1 Bonding ground set

Flow rate: up to 82 l/min (Rotor)*, up to 61 l/min (Impeller)*

Head: up to 9 m (Rotor)*, up to 20 m (Impeller)*

Medium temperature: see Ex-certificate

Viscosity: up to 400 mPas*, **Density:** up to 1.3*

230 V

1442 4110


Drum pump set JP-480 SS 1200

Electric universal motor JP-480, 230 V, 50/60 Hz, 825 W, protection class II 2G Ex db IIC T6 Gb, IP 55, with integrated low voltage release, 5 m cable **without plug**. Optional with Ex-plug.

EC type examination certificate Bureau Veritas **EPS 17 ATEX 1 088 X**

IECEX Certificate of Conformity **IECEX EPS 17.0045 X**

Pump tube: Stainless steel 316Ti, sealless, 1.200 mm, outer-Ø 41 mm, connection thread G 1¼",

EC type examination certificate number **ZELM 09 ATEX 0424 X**

2 m Multi purpose hose, conductive 1" (NW 25)

2 Hose connectors Stainless steel IG 1¼" or IG 1"

1 Nozzle Brass nickel plated

1 Bonding ground set

Flow rate: up to 112 l/min (Rotor)*, up to 83 l/min (Impeller)*

Head: up to 16 m (Rotor)*, up to 37 m (Impeller)*

Medium temperature: see Ex-certificate

Viscosity: up to 1000 mPas*, **Density:** up to 1.9*

230 V

1482 4120

BARRELPUMP.IR

Drum pump sets

Further versions
on request

Drum pump sets for chemicals and mineral oil products

Order No.

**Drum pump set JP-AIR 1 SS 1000****Air operated motor JP-AIR 1, 300 W**

at max. 6 bar operating pressure, Motor with Brass valve and muffler for compressed air control.

EC type examination certificate number **IBEx U05 ATEX B007 X**

Pump tube: Stainless steel 316Ti, sealless, 1.000 mm, outer-Ø 41 mm, connection thread G 1 1/4",

EC type examination certificate number **ZELM 09 ATEX 0424 X**

2 m Multi purpose hose, conductive 1" (NW 25)

2 Hose connectors Stainless steel, IG 1 1/4" or IG 1"

1 Nozzle Brass nickel plated

1 Bonding ground set

Flow rate: up to 78 l/min (Rotor)*, up to 60 l/min (Impeller)*

Head: up to 9 m (Rotor)*, up to 13 m (Impeller)*

Medium temperature: see Ex-certificate

Viscosity: up to 400 mPas*, **Density:** up to 1.3*

3012 4110

**Drum pump set JP-AIR 3 SS 1000****Air operated motor JP-AIR 3, 400 W**

at max. 6 bar operating pressure, Motor with Brass valve and muffler for compressed air control.

EC type examination certificate number **IBEx U05 ATEX B007 X**

Pump tube: Stainless steel 316Ti, sealless, 1.000 mm, outer-Ø 41 mm, connection thread G 1 1/4",

EC type examination certificate number **ZELM 09 ATEX 0424 X**

2 m Multi purpose hose, conductive 1" (NW 25)

2 Hose connectors Stainless steel, IG 1 1/4" or IG 1"

1 Nozzle Brass nickel plated

1 Bonding ground set

Flow rate: up to 91 l/min (Rotor)*, up to 71 l/min (Impeller)*

Head: up to 13 m (Rotor)*, up to 25 m (Impeller)*

Medium temperature: see Ex-certificate

Viscosity: up to 600 mPas*, **Density:** up to 1.5*

3032 4110

BARRELPUMP.IR

* All specified values are real measured maximum values.

* Test medium water 20 ° C, pressure pipe 1", oval gear meter 1", measured values: ± 5%

Attention: When using a nozzle, the flow rate is reduced to app. 60-80 l/min

(depends on the pump and application).

All drum pump sets with rotor

Eccentric screw drum and container pumps

JP-700 SR (speed reducer)



▶ Drive with electric or air operated motor and planetary gearbox.

▶ **ATEX**
The JP-700 SR with PTFE stator and a special ATEX mechanical seal has a type-examination certificate and can be used for flammable liquids and in explosive environments.
II 1/2 G c IIA T4



Description

- Particularly for intermittent operation.
- For gentle and almost pulsation free transferring of low viscous to highly viscous, thixotropic, gassy, solids and fibres containing, aggressive and neutral media.
- Pump tube will be driven by electric universal or air operated motors.
- All pump parts are made of Stainless steel 316Ti.
- The stators are adapted to the medium and available in NBR, NBR light, FKM, EPDM, EPDM light, PTFE.
- Flow rate 12, 25 or 50 l/min (at JP-700 DR also dosing pumps are available!).
- Discharge pressure 6 bar at the single-stage and 12 bar with the two-stage pump tubes.
- The maximum viscosity of the medium is 10.000 mPas at the SR version.
- Medium temperature up to 150 °C.
- Standard pump tube lengths are 700, 1.000 and 1.200 mm. Special lengths up to 2.000 mm on request.
- Suction tube diameter 54 mm, therefore for all 200 liter drums with a 2" bung hole.
- Easy disassembling and therefore optimal cleaning. Weight 12 kg.

- Shaft seal by single-acting mechanical seal or stuffing box packing.
- Special version for food, cosmetic and pharmaceutical products can be delivered: polished surfaces, either open or encapsulated pin joints, no dead spaces in the pump, easy disassembling and therefore easy cleaning, milk thread connection DN 11851, CIP connections as an option, stator and sealing materials in food grade FDA, also PTFE stators available.

Examples of media

Standard version suitable for:

Chemical products

- | | |
|-----------|--------------------|
| Paints | Latex |
| Varnishes | Silicone compounds |
| Resins | Polymers |

Petroleum products

- | | |
|------|--------------|
| Oils | Cutting oils |
| Fats | Refrigerant |

In addition a special version for use in hazardous areas as well as a version for the food industry is available.

PUMP TUBES

Suction tube Ø 54 mm, at discharge male thread connection G 1 1/2"
Optional hose connection 1", 1 1/4" or 1 1/2"
SR-Version (with planetary gear = speed reducer) ca. 700 U/min.

MOTORS



Model	Suction tube length	Flow rate	Pressure	JP-AIR2 / Ex-proof	JP-AIR3 / Ex-proof	JP-280	JP-480 / Ex-proof
JP-700.12.1	700/1.000/1.200 mm	12 l/min	6/2 bar	600 W at max. 6 bar operating pressure, ATEX	400 W at max. 6 bar operating pressure, ATEX	825 W Electric motor 230 V, 50/60 Hz	825 W Electric motor 230/115 V, 50-60 Hz, ATEX
JP-700.12.2	800/1.100/1.300 mm	12 l/min	12/3 bar	Air operated motor, with starting button on the handle. The motor starts running and the pump is transferring media when the button is pressed.	Air operated motor, stainless steel housing with plug valve at air intake for compressed air control. This regulates the motor speed and varies the pumping capacity.	Double insulated class II, splash proofing acc. IP 24. On/off switch, over load protection switch	Protection class II 2G Ex db IIC T6 Gb, IP 55. On/off switch, over load protection, 5 m cable without plug.
JP-700.25.1	700/1.000/1.200 mm	25 l/min	6/2 bar				
JP-700.25.2	800/1.100/1.300 mm	25 l/min	12/3 bar				
JP-700.50.1	700/1.000/1.200 mm	50 l/min	6/2 bar				
JP-700.50.2	800/1.100/1.300 mm	50 l/min	12/3 bar				

Eccentric screw drum and container pumps with three-phase-, gear-, single-phase- or air operated motor

Description

- The pumps of the series **JP-700 DR, - FK** are versatile, robust and powerful. They are used for transferring thin fluid to highly viscous substances up to 100.000 mPas, **preferably used stationarily and in continuous operation.**
- **JP-700 DR, - FK** - Version drive, by three-phase-, gear-, single-phase- or air operated motors.
- All pumps that get in contact with the media are made of Stainless steel 316Ti.

- **The stators** are available in NBR, NBR light, FKM, EPDM, EPDM light or PTFE depending on the medium.
- **The pump tube sealing** is designed as a mechanical seal or stuffing box.
- The weight of the pump depends on suction tube length and the drive 25–35 kg.
- The pump is also available as a food version (see JP-700 SR version) or as a dosing pump (lower flow rate, smaller suction tube diameter).

► Drive with three-phase or air operated motor is directly coupled with flexible coupling, beared shaft ball.

► **ATEX**
The JP-700 DR with PTFE stator and a special ATEX mechanical seal has a type-examination certificate and can be used for flammable liquids and in explosive environments.
II ½ G c IIA T4



Examples of media

Standard version suitable for:

- | | |
|----------|---------------|
| Sludges | Honey |
| Pastes | Syrup |
| Soap | Jams |
| Shampoos | Ketchup, etc. |

In addition, a special version for use in hazardous areas as well as a version for the food industry is available.

► Drive with three-phase or air operated motor directly coupled with extended motor shaft.

PUMP TUBES

Suction tube Ø 54 mm, at discharge connection male thread G 1½"

Optional hose connection 1", 1¼" or 1½"

JP-700 DR version driven by three-phase, gear-, single-phase- or air operated motors.

Wide range of accessories such as pump hanger, double-sided carrying handle, bypass or dry running protection available as an option.

MOTORS



Model	Suction tube length	Flow rate	Pressure
JP-700.12.1 DR	700/1.000/1.200 mm	12 l/min	6/2 bar
JP-700.12.2 DR	800/1.100/1.300 mm	12 l/min	12/3 bar
JP-700.25.1 DR	700/1.000/1.200 mm	25 l/min	6/2 bar
JP-700.25.2 DR	800/1.100/1.300 mm	25 l/min	12/3 bar
JP-700.50.1 DR	800/1.100/1.300 mm	50 l/min	6/2 bar
JP-700.50.2 DR	900/1.200/1.400 mm	50 l/min	12/3 bar

Three-phase motor
230/400 V, 50 Hz
0,37–2,2 kW

Three-phase gear motor
230/400 V, 50 Hz
0,37–2,2 kW

Air operated lamellar motor
0,5–1,5 kW, 900 rpm at 6 bar

Other flow rates and voltages on request.


Single-phase motor 230 V optional.

Reduced speed at high viscosities or for abrasive media, optimal speed for requested flow rate.

JP-AIR 4 (0,5 kW)
JP-AIR 6 (1,0 kW)
JP-AIR 8 (1,5 kW)

Eccentric screw container pumps

JP-700.80.1, 80.2, 200.1, 200.2, 300.1 and 300.2



Description

- Gentle and nearly pulsation free pumping of low to high viscous, thixotropic, gaseous, solids and fibers containing, aggressive and neutral media.
- Suction tube and pump parts of 316Ti, rotor made of Stainless steel 316Ti.
- Pump and motor directly coupled.
- Encapsulated pin joints or joint-free.
- Easy disassembly.
- Flow rates 80, 200 or 300 l/min.
- Discharge pressure 6 and 12 bar.
- Pump tube lengths 1.000, 1.200 and 1.400 mm (special lengths available).
- Suction tube diameter 89 mm (JP-700.80), 105 mm (JP-700.200) and 130 mm (JP-700.300).
- Various discharge connections.
- Hose connection DN 40, DN 50–65, DN 65–80.
- Materials of the shaft seal: mechanical seal SS/Carbon FKM or SiC/SiC/FKM. O-rings made of FKM or FEP. Alternatively stuffing box made of PTFE.

- Driven by three-phase, gear- or air operated motors.
- **Special features of the food version:** Polished surfaces, easy disassembly and thus easy to clean at the discharge milk thread DIN 11851, stator and seals in food grade version according to FDA, PTFE stators also available.

Examples of media

Standard version suitable for:

Chemical products:



Paints	Latex
Varnishes	Silicone compounds
Resins	Polymers

Petroleum products:

Oils	Cutting oils
Fats	Refrigerant

Food:

Fruit juices	Tomato paste
Concentrates	Syrup/Honey



Selection of stators (valid for all pumps)

- NBR black max. 90 °C, suitable for oily and greasy media, alcohol and aqueous solutions.
Not resistant to acids, alkalies and solvents.
- NBR White Nitrile, max. 90 °C, suitable for oily and greasy media, alcohol and food.
Not resistant to acids, alkalies and solvents.
- FKM max. 160 °C, high chemical resistance.
- PTFE max. 200 °C, high chemical resistance, suitable for food, pharmaceutical and cosmetic products.
- EPDM max. 110 °C, good resistance to alkalies (undiluted and diluted), acids (diluted), ketones, alcohols.

Food-safe (corresponding to BGVV recommendations and in the composition of the positive list of FDA).

Not resistant to oils and fats when transferring milk (3.5% fat) a sufficient resistance is given.

Information needed to select the right high viscosity pump

Based on your specific applications we need:

- Specification of the liquid
- Viscosity and medium temperature
- Density
- Required flow rate
- Head including pipe losses
- Content as well as type and size of solids
- Will the pump be used mobile or stationary, vertical or horizontal?
- Operating hours per day

Electric and pneumatic driven drum and container pumps

JESSBERGER pump technology with internal and external cooled electric motors or pneumatic motors (also ex-protected) in different engine-power classes. Sealless pump tubes in Polypropylene, PVDF, ALU and Stainless Steel SS 316. Pump tube lengths 700, 1.000, 1.200, 1.500 and 1.800 mm. Special lengths up to 3.000 mm on request.



Eccentric screw pumps JP-700 for drums and containers with electric or pneumatic motor

are suitable for transferring thin to high viscous substances (max. 100.000 mPas) and will be used particularly stationarily or for continuous work. All pump parts are made of Stainless steel SS 316Ti. Stators are available in NBR, NBR light, FKM, EPDM, EPDM light or PTFE.




High viscosity dosing pumps

for thin fluid, viscous, neutral and aggressive media with or without particles.

Horizontal eccentric screw pumps

are suitable for liquids with low or high viscosity, whether neutral or aggressive, with or without solids or fibres particles.



Manual hand operated drum pumps


are lightweight and handy devices for almost all low-viscous media.

JP-03 pump made of PP, shaft made of tool steel, seals made of NBR, suitable for oils, diesel, alcohol up to 50%, anti freezing liquid (diluted), water, etc.

JP-04 pump and shaft made of PP, seals depending on medium: FKM (acids), EPDM (alkalies), NBR (oils) and Fluoropolymer (low-viscous food).

JP-05 pump made of Stainless steel 316Ti, seals made of PTFE, suitable for flammable media like solvents and low-viscous food.

JP-07 pump made of PP, internal parts also made of Stainless steel, seals depending on medium: FKM (lightly acids), EPDM (alkalies) and NBR (mineral oil products).



Small filling plant

Low-viscous up to lightly viscous media can be filled fast and exact out of drum and containers in manually supplied bottles and canisters at the push of a button.



Air-operated diaphragm pumps

JESSBERGER diaphragm pumps are suitable for nearly all areas of use. They are capable of pumping aggressive and flammable substances, high viscous liquids also with solids or fibre particles and media containing gas from 5 l/min up to 1.050 l/min.



Sealless magnetic driven pumps

Various sizes, state-of-the-art construction, sealless and environmentally friendly, suitable for a variety of uses. Smooth and quiet operation, long operating time, easy to maintain.



Vertical centrifugal pumps

Executions in Polypropylene and PVDF

Horizontal centrifugal pumps

Executions in Polypropylene and PVDF



Mixers and agitators

JESSBERGER offers solutions for almost every mixing application for drums and containers.

Dosing pumps

Diaphragm or plunger metering pump.



Electric diesel and heating oil pumps

for refueling the motors of vehicles that are driven with diesel or heating oil of hazard class A III like tractors, agricultural machines and machines for construction work, trucks and motor boats.



Hoses

PVC hoses, conductive universal-chemical and solvent hoses made of EPDM, conductive multipurpose-chemical hoses made of PE, PTFE hoses, mineral oil hoses, food hoses, special hoses on request.

Please require detailed information about the individual product groups of the JESSBERGER delivery program.

Please make a cross next to the requested products and fax or e-mail this page to us with your address.

BARRELPUMP.IR

JESSBERGER GmbH

Jaegerweg 5-7

D-85521 Ottobrunn

Phone +49 (0) 89 - 66 66 33 400

Fax +49 (0) 89 - 66 66 33 411

info@jessumpen.de

www.jessumpen.com