

## Product overview

- Manual hand pumps
- Laboratory pumps
- Drum- and container pumps
- Vertical eccentric screw pumps
- Horizontal eccentric screw pumps
- High viscous dosing pumps
- Drum emptying- and filling plants
- Air operated diaphragm pumps
- Horizontal centrifugal pumps
- Vertical centrifugal pumps
- Magnetic centrifugal pumps
- Diesel- and heating oil pumps
- Pump accessories



For all media  
e.g. for oils,  
chemicals,  
flammable media  
and high viscous  
fluids



Made in Germany



ATEX 2014/34/EC



Proofed Quality

## Decades of experience in barrel pump business

The family-run company JESSBERGER headquartered in Ottobrunn near Munich is manufacturer of electric and pneumatic driven drum and container pumps, vertical and horizontal eccentric screw pumps, dosing pumps for high viscous media, hand operated pumps and a comprehensive range of accessories like flowmeters, nozzles, etc.

Air operated diaphragm pumps, horizontal centrifugal pumps (also available as magnetically coupled sealless centrifugal pumps) and vertical centrifugal pumps complete the delivery program beside further industrial pumps.

Thanks to long time employees and the firm owners the company pides itself on a long and substantial experience in pump business. Although the brand JESSBERGER exists as a firm name in drum pump business only since beginning 2003, the company has developed within a short time to a real alternative. The intention was to set new standards in price at coexisting highest quality – which was succeeded impressively.

The good reputation of JESSBERGER in drum pump business is a result of a personal, expert advice through our team, a maximum flexibility in all areas of the company and a direct contact with the customers.

The company owners have set themselves the goal of having a very close and personal contact with their customers – not only by exhibiting on many trade shows each year. Furthermore, they want to demonstrate their flexibility that is based on a clear arranged company structure at delivery times and special customers' requests.

Qualified partners in Germany, Europe and all over the world complete this concept and guarantee a nearly optimized customer support.

The company leadership and the technical management attach the greatest importance to a strict quality control. The complete production and assembling area are organized in accordance to the quality man-



agement system DIN EN ISO 9001:2015 and for the Stainless steel pump tubes, the electric Ex-motors JP-400, 440, 460, 480, the air operated motors JP-AIR 1, JP-AIR 2 and JP-AIR 3 and some eccentric screw pumps in accordance to ATEX 2014/34/EC (explosion prevention and protection).

Annual external and internal inspection audits assure the compliance with these regulations and ensure the high quality standards. This pronounced awareness of quality and the experience for decades in drum pump business guarantee a high quality of the pumps at a very attractive price.

Convince yourself of the advantages of JESSBERGER and the quality made in Germany!

### Our advantages

- Owner operated family company
- Decades of experience in drum pump business
- Quality made in Germany
- Optimal price/performance ratio
- Personal and expert advice, the best possible customer service
- Maximum flexibility in all company divisions
- Certified acc. to ISO 9001: 2008 and ATEX 2014/34/EC

Since March 2008 the pump manufacturer has its new head office in Ottobrunn. In February 2018, the available industrial area more than doubled due to the acquisition of the neighbouring building. More than 900 sqm production/stock and 700 sqm office will ensure a further sustained economic growth and the possibility to fulfill special customers' requests. The construction and production of the eccentric screw pumps are based at a second facility in Upper Bavaria.

### Laboratory-, drum and container pumps

**Drum and container pumps with electric or air operated motors (also as laboratory pumps or ATEX certified available) can be used for nearly all kind of media whether thin fluid or middle viscous (max. 1.000 mPas), neutral or aggressive, flammable or non easily combustible.**

- Electric universal motors in 230, 115 or 24 Volt in different power and protection classes.
- Air operated motors (for max. 6 bar operating pressure).
- Pump tubes in PP, PVDF, Aluminium or Stainless steel.
- Flow rates up to 112 l/min (with 1" hose).
- Pressure up to 3.7 bar (with impeller for high pressure).
- Mixing pump tubes or complete drum emptying as an option.
- Pump tube lengths in 700, 1.000, 1.200, 1.500, 1.800 mm.
- Special lengths from 200 mm up to 3.000 mm on request.

### Vertical eccentric screw pumps JP-700 SR

**Vertical eccentric screw pumps with single phase or air operated motors (also ATEX certified available) are suitable for a gentle and low-pulsation transferring of thin fluid up to viscous media (max. 20.000 mPas) out of drums and containers. They will be used as portable or stationary pumps for short operation times.**

- Electric universal motors in 230 and 115 Volt or air operated motors (for max. 6 bar operating pressure).
- Pump tubes in Stainless steel 316Ti.
- Stators made of NBR, NBR light, EPDM, EPDM light, FKM, PTFE (depending on the type of medium).
- Standard flow rates of 12, 25 or 50 l/min.
- Discharge pressures of 6 (one stage) or 12 bar (two stages).
- Pump tube lengths in 700, 800, 900, 1.000, 1.100, 1.200, 1.300, 1.400 mm.
- Special tube lengths and models on request.



For oils, chemicals, flammable and high viscous media

BARRELPUMP.IR

**Vertical eccentric screw pumps JP-700 DR**

Eccentric screw pumps with three phase, gear or air operated motors (also ATEX certified available) are suitable for a gentle and low-pulsation transferring of thin fluid up to high viscous media (max. 100.000 mPas) out of drums and containers.

They will be used particularly as stationary pumps and especially for continuous operation times.

- Three phase, gear or air operated motors in different power and protection classes.
- Pump tubes in Stainless steel 316Ti.
- Stators made of NBR, NBR light, EPDM, EPDM light, FKM, PTFE (depending on the type of medium).
- Flow rates of 12, 25 or 50 l/min. at drum pump or 80, 200 or 300 l/min. at container pump.
- Discharge pressures of 6 (one stage) or 12 bar (two stages).
- Pump tube lengths in 700, 800, 900, 1.000, 1.100, 1.200, 1.300, 1400 (drum pump) or 1.000, 1.200, 1.400 mm (container pump).
- Special tube lengths and models on request.




**Horizontal eccentric screw pumps JP-700H**

Horizontal eccentric screw pumps with three phase, gear or air operated motors provide a gentle, low-pulsation transferring of thin fluid up to high viscous (max. 100.000 mPas), thixotropic, gas containing, particles or fibres containing, aggressive or neutral media.

These pumps will be used particularly as stationary pumps and especially for continuous operation times.

- Three phase, gear or air operated motors in different power and protection classes.
- Pumps in Stainless steel 316Ti or Cast iron.
- Stators made of NBR, NBR light, EPDM, EPDM light, FKM, PTFE (depending on the type of medium).
- Flow rates up to 200 m³/h.
- Discharge pressures of 6, 12, 18 or 24 bar.
- A dry-run protection prevents the operation of eccentric screw pumps without liquid (optional).

Low-pulsation and gentle transport of thin to highly viscous media



**Dosing pumps**



High viscosity dosing pumps are especially suitable for a low-pulsation transferring and dosing of thin fluid up to high viscous media (max. 100.000 mPas), thixotropic, gas containing, particles or fibres containing, aggressive or neutral media.

- Gear motor suitable for operation with frequency inverter or gear motor that is adjustable via hand.
- Pumps in Stainless steel 316Ti.
- Stators in NBR, NBR light, EPDM, EPDM light, FKM, PTFE (depending on the type of medium).
- Flow rate from 0,6 up to 600 l/h.
- Discharge pressures of 6 (one stage) or 12 bar (two stages).

**Drum emptying and filling plants**



Complete filling and dosing plants for exact dispensing of small quantities.

Safe and easy transfer of various types of media from containers.

- System filling plant/drum pump for the exact filling of empty or partially filled containers.



Drum emptying systems are suitable for a clean and fast emptying of open drums and containers with high viscous up to pasty media that can not flow by itself into the pump any more.

BARRELPUMP.IR

## Spare parts for eccentric screw pumps

At wear parts a short delivery time is important as well as quality and price.

Our program of spare parts for nearly all well known third parties includes:

- Rotors and stators.
- Drive shafts.
- Coupling rods.
- Turning work pieces in different materials.
- Mechanical seals, glands or O-rings, etc.

## Manual hand pumps

Manual hand operated pumps are light and handy devices for an easy and safe emptying of thin fluid up to middle viscous media (max. 1.000 mPas) out of small canisters or 60 and 200 liter drums.

- Designed as hand lever or rotating pump.
- Different pump materials and seals depending on the medium. The hand operated pumps can be divided in following groups:
  1. For acids and alkalies.
  2. For non flammable mineral oil products.
  3. For easy flammable media like solvents.
  4. For food and beverage products.
- Pump tube lengths for canisters and drums.
- Flow rates from 0,3 l/stroke up to 1 l/rotation.
- Drum adapter with male thread G 2", adapters available.

## Air operated diaphragm pumps

Air operated diaphragm pumps JP-800, JP-810 are suitable for nearly all areas of use. They are self priming, can run dry and are capable of pumping aggressive, flammable and viscous media (max. 55.000 mPas, depending on type of pump), also with particles or media containing gas.

- Pump bodies in PP, PVDF, Aluminium or Stainless steel.
- Flow rates from 5 l/min. (1/4") up to 1050 l/min. (3").
- Max. operating pressure of 8 bar.
- Transformation ratio 1:1, special type series with ratio 2:1 or 3:1 as high pressure pumps for filter presses.
- Certificate for Ex-zone 2, conduct version for Ex-zone 1.
- Special executions for food and sanitary products.

## Horizontal centrifugal pumps



The pumps of the series JP-840 are suitable for the rapid pumping of chemicals during the emptying of containers or for applications where a medium has to be kept in circulation.

- Three phase motor, 230/400 Volt, 50 Hz, IP 55, 2900 rpm.
- Pump bodies in Polypropylene or PVDF.
- Flow rates from 6 up to 75 m<sup>3</sup>/h.
- Delivery head up to 38 m.
- Maximum viscosity 500 mPas (at 20 °C).
- Special models (higher flow rates, pumps made of Stainless steel, self priming, dry running or Ex-protected pumps) on request.

## Sealless magnetic centrifugal pumps



These magnetically coupled centrifugal pumps are tight and absolutely free of leakage due to their non-contact torque transmission.

- Pump bodies in Polypropylene or PVDF.
- Flow rates depending on pump model and type series.
- Special models on request.




BARRELPUMP.IR

## Vertical centrifugal pumps

In case of wear parts, it is not only a short delivery time, but also the quality and price that is important.

The availability of different materials of construction – depending on chemical and thermal resistance of medium or environment – guarantees an absolute reliability of operation as well as a long life time of the pump.

- Three phase motor, 230/400 Volt, 50 Hz, IP 55, 2900 rpm.
- Pump bodies in Polypropylene or PVDF.
- Pump tube lengths 250, 500, 800, 1.000, 1.250 mm.
- Flow rates from 6 up to 75 m<sup>3</sup>/h.
- Delivery head up to 38 m.
- Maximum viscosity 500 mPas (at 20 °C).
- Special tube lengths and models (f.e. Stainless steel) on request.



## Pump accessories

### Accessories for pumps

- Drum adapters, emission proof adapters, thread adapters.
- Strainers made of PP, Stainless steel or PVDF (for protection of drum pump if particles are present).
- Manual nozzles made of PP, PVDF, Aluminium or Stainless steel, automatic nozzles for fuel or diesel.
- Hoses in different materials for transferring nearly all kind of media (PVC-hoses, Universal chemical and solvent hoses, mineral oil and food grade hoses, etc.).
- Turbine wheel or oval gear flowmeters made of PP, PVDF, Aluminium or Stainless steel (also Ex-protected), impulse output or preselection of flow rate for controlling a pump or magnetic valve.



## Diesel- and heating oil pumps

Diesel- and heating oil pumps are especially suitable for refueling the motors of vehicles that are driven with diesel like tractors, agricultural machines and machines for construction work, trucks and motor boats. They also facilitate the filling of heating oil.

- Protank 30 (at the beginning non self priming).
- Protank 50 (self priming).
- Pump models in 230, 12 and 24 Volt.
- Flow rates from 31 up to 50 l/min.
- Delivery head from 9 up to 17 m.
- Set with 1,6 m suction hose, 4 m discharge hose and nozzle (manual or automatic one).
- Flowmeters as an option.



## JESSBERGER GmbH

Jaegerweg 5-7  
D-85521 Ottobrunn  
Phone +49 (0) 89 - 66 66 33 400  
Fax +49 (0) 89 - 66 66 33 411  
info@jessumpen.de  
www.jessumpen.com